



T.C. Ticaret Bakanlığı
İthalat Genel Müdürlüğü

Değerli Sanayicilerimiz;

Bilindiği üzere, sanayicimizin ihtiyaç duyduğu hammadde ve yarı mamul niteliğindeki sanayi ürünlerine ilişkin olarak üretimi olmayan ürünlerde gümrük vergilerinin askıya alınması, üretimi tüketimi karşılamayan ürünlerde ise tarife kontenjanı açılmasına ilişkin başvurular, ülkemiz temsilcilerinin de katıldığı toplantılarda Avrupa Komisyonu ile müzakere edilerek karara bağlanmakta ve düzenlemeler her yıl 1 Ocak ve 1 Temmuz tarihlerinde yürürlüğe girmektedir.

Bu çerçevede, Avrupa Birliği (AB) ya da Türk firmalarınca 01/01/2026 tarihinden itibaren gümrük vergilerinin askıya alınması veya tarife kontenjanı uygulanması ya da mevcut gümrük vergisi indirimlerinin kaldırılması talep edilen eşyaya ilişkin liste Ek-1’de, hali hazırda gümrük vergileri askıya alınmış olan eşyaya ilişkin liste Ek-2’de, AB tarafından tarife kontenjanı açılmış olan eşyaya ilişkin liste Ek-3’te, ülkemiz tarafından tarife kontenjanı açılmış olan eşyaya ilişkin liste ise Ek-4’te yer almaktadır.

Bu itibarla; üretici firmalarımızın Ek-1’de yer alan gümrük vergilerinin askıya alınmasına ilişkin taleplere dair itirazlarını, eş başvuru taleplerini ya da bu listede bulunan itiraz başvurularına ilişkin mevcut askıya almaların yürürlükte kalmasına dair taleplerini **6 Haziran 2025** tarihine kadar; Ek-2, Ek-3 ve Ek-4’te yer alan eşyada hali hazırda uygulanan indirimli gümrük vergisi uygulamalarının sonlandırılmasına ilişkin taleplerini ise **7 Mayıs 2025** tarihine kadar resmi yazı ile Ticaret Bakanlığı İthalat Genel Müdürlüğüne iletmeleri gerekmektedir.

Başvuruların en son belirtilen tarihlere kadar tam ve eksiksiz olarak firmaların Kayıtlı Elektronik Posta (KEP) adreslerinden Ticaret Bakanlığı KEP adresine (ticaretbakanligi@hs01.kep.tr) elektronik ortamda iletilmesi gerekmektedir.

Başvurulara ilişkin detaylı bilgi ve formlara <https://www.ticaret.gov.tr/ithalat/askiya-alma-ve-tarife-kontenjan/askiya-alma-sistemi> adresinden ulaşılabilir.

Bilgileri ile konunun önemine binaen üyeniz firmalara eksiksiz olarak duyurulması hususunda gereğini rica ederim.

Not: Askıya alma sistemine ilişkin detaylı bilgi için 2025/18 sayılı Askıya Alma Sistemine İlişkin Tebliğ (İthalat: 2025/18) incelenebilir. Ayrıca; listede yer alan ürünlerin özel tanımlı olmasından dolayı, firmalar tarafından GTP’den ziyade ürün tanımlarının incelenmesi gerekmektedir.

Müge DAĞLI
Bakan a.
Daire Başkanı

Kerim HEMDİL
Bakan a.
Daire Başkanı

Sinan YANAZ
Bakan a.
Daire Başkanı

İlgili Kişilerin İletişim Bilgileri:

Kimyasallar ve Tekstil Hammaddeleri:

| | | | |
|-----------------------|------------------|--------------------|------------------------------|
| - Bekir Sıddık KIZMAZ | Uzman | T: 0 312 204 99 12 | E: kizmazb@ticaret.gov.tr |
| - Furkan Eren KAHVECİ | Uzman | T: 0 312 204 95 77 | E: kahvecif@ticaret.gov.tr |
| - Ekin Deniz GÖÇÜK | Uzman | T: 0 312 204 95 70 | E: timured@ticaret.gov.tr |
| - Mehmet BARAN | Uzman Yardımcısı | T: 0 312 204 95 81 | E: m.baran2@ticaret.gov.tr |
| - Ali YANAR | Uzman Yardımcısı | T: 0 312 204 99 74 | E: a.yanar3@ticaret.gov.tr |
| - Furkan DEMİRCİ | Uzman Yardımcısı | T: 0 312 204 92 93 | E: f.demirci5@ticaret.gov.tr |
| - Serdar AKÇAY | Uzman Yardımcısı | T: 0 312 204 98 83 | E: s.akcay2@ticaret.gov.tr |

Maden Metal ve Nakil Vasıtaları:

| | | | |
|---------------------|------------------|--------------------|---------------------------------|
| - Sude GÜRCAN | Uzman | T: 0 312 204 94 92 | E: gureans@ticaret.gov.tr |
| - Elif Tuğçe KANAK | Uzman | T: 0 312 204 94 90 | E: e.katircioglu@ticaret.gov.tr |
| - Öznur ÖNAL | Uzman | T: 0 312 204 91 89 | E: o.onal4@ticaret.gov.tr |
| - Fatma Hilal YÜNEY | Uzman Yardımcısı | T: 0 312 204 92 96 | E: yuneyf@ticaret.gov.tr |

Makine, Elektrik ve Elektronik:

| | | | |
|-----------------------|------------------|--------------------|---------------------------------|
| - Tuğba Köse SANDALCI | Uzman | T: 0 312 204 99 30 | E: sandalcit@ticaret.gov.tr |
| - Ceren Koç PEKTEZEL | Uzman Yardımcısı | T: 0 312 204 96 68 | E: c.kocpektezel@ticaret.gov.tr |
| - Bilgenur ÜÇGÜL | Uzman Yardımcısı | T: 0 312 204 99 66 | E: b.ucgul@ticaret.gov.tr |
| - Gamze ÖZGÜN | Uzman Yardımcısı | T: 0 312 204 87 60 | E: g.ozgun@ticaret.gov.tr |

CYCLE 2026-01

Sorting order:

A – first 'quotas', then 'suspensions'

B – **new** requests, **amending** requests.

>>>The duty suspension and quota requests on the following list are currently under discussion. The data available on this list may not represent the final state of the discussions within the relevant Commission Working group.

Please note that it cannot be guaranteed that the information available exactly reproduces an officially adopted text. Only European Union legislation published in the Official Journal of the European Union is deemed authentic<<<

| CN code | TARIC | Reference Mail | Working Number | Description | <u>Quotas</u> | New or amendment request | Measure status | Partner Position Country | Partner Position | Public Comments |
|------------|-------|----------------|----------------|---|--|--------------------------|-------------------|--------------------------|-------------------|---|
| 2920 29 00 | | 2171443/2025 | 1329 | Fosetyl-sodium (CAS RN 39148-16-8) in aqueous solution with a fosetyl-sodium content (CAS RN 39148-16-8) of 39 but not more than 41 w/w | Q/521tonnes, 01.01-31.12 | New | UNDER EXAMINATION | DE | Applicant | Round 2026.1 to be used in the production of plant protection product (fungicide) |
| 2921 41 00 | | 2376650/2025 | 1318 | Aniline with a purity of 99 % by weight or more | Q/50000tonnes, 01.01-31.12 | New | UNDER EXAMINATION | DE DE | Applicant Opposed | Round 2026.1 used in the production of methylenediphenyl diisocyanate for manufacturing polyurethanes |
| 2922 19 00 | | 2510155/2025 | 1331 | Triisopropanolamine (Tipa) with a purity by weight of 85 % or more (CAS RN 122-20-3) | Q/7568000kilo grams, 01.01-31.12 | New | UNDER EXAMINATION | TR | Applicant | Round 2026.1 to be used in the cement industry |
| 3907 29 20 | | 2365539/2025 | 1316 | Polyether Polyol compromising sucrose starters modified with sorbitol, DEG and palm oil as a mixture by weight of; - Propoxylated sucrose 50 % or more but not more than 70 % (CAS RN 9049-71-2) | Q/28200000kilograms, 01.01-31.12 | New | UNDER EXAMINATION | TR | Applicant | Round 2026.1 to be used in the formulation of Polyurethane Foam |

| | | | | | | | | | | |
|---------------|----|--|------|--|---|-----------|-------------------|-------|-------------------|---|
| | | | | <ul style="list-style-type: none"> - Propoxylated sorbitol 5 % or more but not more than 15 % (CAS RN 52625-13-5) - Propoxylated DEG 10 % or more but not more than 20 % (CAS RN 9051-51-8) - Propoxylated Palm Oil 10 % or more but not more than 15 % (CAS RN 512802-65-2) <p>with a hydroxyl number of 410 or more but not more than 460 according to ASTM 4272 method and a viscosity index of 4 000 or more but not more than 7 000 mPas@25C according to ASTM D 4878 method</p> | | | | | | |
| 3920 59 90 | | 2265836/2025 | 1330 | <p>Acrylic Film with:</p> <ul style="list-style-type: none"> - a total thickness of 53 (um), - total transmittance of 92 % - haze value of 0,9 % - 60 degree gloss of 147 % - heat shrinkage of -4/-1 % MD/TD - tensile strength (Mpa) of 47/43 MD/TD - elongation at break of 113/118 MD/TD - glass transition temperature of 10 (Celcius) | Q/7883544square meters, 01.01-31.12 | New | UNDER EXAMINATION | TR | Applicant | Round 2026.1 to be used in the production of PVC decorative film |
| ex 2932 19 00 | 85 | 6819955/2024 | 5245 | 2-Methyltetrahydrofuran (CAS RN 96-47-9) with a purity by weight of 99 % or more | Q/1500tonnes, 01.01-31.12 | Amendment | UNDER EXAMINATION | BE BE | Applicant Opposed | Round 2026-01 - request for amendment. Round 2025/7 to be used in chemical formulation mainly for pharma industry |
| ex 3811 29 00 | 83 | 452962/2013 PROLONG 2020 Prologation exercise 1/1/2019 | 5000 | <p>Additives, consisting of the reaction products of 1,3,4-thiadiazolidine-2,5-dithione with hydrogen peroxide and tert-nonanethiol, containing by weight:</p> <ul style="list-style-type: none"> - 70 % or more of 2,5-bis(tert-nonyldithio)-[1,3,4]-thiadiazole (CAS | Q/500tonnes, 01.01-31.12 | Amendment | UNDER EXAMINATION | FR | Applicant | Round 2026-01-amendment./ Round 2025-07 - amendment will be accepted in the next round/. |

| | | | | | | | | | | |
|--------------------------------|----------|--|------|---|------------------------------------|-----------|----------------------|----------|----------------------|---|
| | | | | RN 89347-09-1), and - 10 % or more of 5-(tert-nonyldithio)-1,3,4-thiadiazole-2(3H)-thione (CAS RN 97503-12-3), for use in the manufacture of blends of additives for lubricating oils (1) | | | | | | |
| 7601 20 30 7601 20 40 | | 275125/2013 PROLONG 2019 PROLONG 2024 PROLONG 2025 | 5107 | Slabs and billets of unwrought aluminium alloys | <u>Q/573000tonnes, 01.01-31.12</u> | Amendment | UNDER EXAMINATION | EU EU | Applicant Opposed | Round 2026-01 - review of the measure. |
| ex 9029 20 31 ex 9029 90 00 | 40 40 | 3033673/2014 | 5126 | CZ new proposal: Clustered instrument panel with: - -or without stepping motors, - -analog or digital pointers and dials, - -or without microprocessor control board, - -or without LED indicators or LCD display, - -showing at least: - speed, - engine revolutions, - engine temperature, - the fuel level, - -communicating via CAN-BUS and/or K-LINE protocols, for use in the manufacture of goods of Chapter 87 --- Current description: Clustered instrument panel with: - stepping motors, - analog pointers and dials, | <u>Q/160000pieces, 01.01-31.12</u> | Amendment | UNDER EXAMINATION | SK | Applicant | Round 2026-01 request for amendment.// |

| | | | | | | | | | | |
|--|--|--|--|--|--|--|--|--|--|--|
| | | | | <ul style="list-style-type: none">- or without microprocessor control board,- or without LED indicators or LCD display,- showing at least:- speed,- engine revolutions,- engine temperature,- the fuel level,- communicating via CAN-BUS and/or K-LINE protocols, for use in the manufacture of goods of Chapter 87 (1) | | | | | | |
|--|--|--|--|--|--|--|--|--|--|--|

| CN code | TARIC | Reference Mail | Working Number | Description | Suspensions | New or New request | Measure status | Partner Position Country | Partner Position | Public Comments |
|------------|-------|----------------|----------------|---|-------------|--------------------|-------------------|--------------------------|------------------|--|
| 2811 22 00 | | 2410551/2025 | 1320 | Silicon dioxide with a purity by weight of 98 % or more CAS RN 112926-00-8 | S | New | UNDER EXAMINATION | RO | Applicant | Round 2026.1 to be used in tyre production |
| 2827 49 90 | | 2073341/2025 | 1019 | Zirconium dichloride oxide (CAS RN 7699-43-6) of a purity by weight of 95 % or more | S | New | UNDER EXAMINATION | AT | Applicant | Round 2026/01: For use in the production of bioceramics |
| 2903 29 00 | | 1710781/2025 | 1002 | trans-1,2-Dichloroethylene (CAS RN 156-60-5) with a purity by weight of 99 % or more | S | New | UNDER EXAMINATION | FR | Applicant | Round 2026/01: used in the manufacture of cleaning solvents |
| 2905 39 95 | | 2159167/2025 | 1020 | Propane-1,3-diol (CAS RN 504-63-2) with a purity by weight of 99 % or more | S | New | UNDER EXAMINATION | BE | Applicant | Round 2026/01: For use in the production of refrigerants, heat transfer fluids |
| 2905 39 95 | | 2030799/2025 | 1015 | 2,5,7,10,11,14-hexaoxa-1,6-distibabicyclo[4.4.4]tetradecane (CAS RN 29736-75-2) with a purity by weight of 99 % or more | S | New | UNDER EXAMINATION | ES | Applicant | Round 2026/01: Used in the production of PET (polyethylene terephthalate) |
| 2906 29 00 | | 1964394/2025 | 1012 | (2-Bromo-5-iodophenyl)methanol (CAS RN 946525-30-0) with a purity by weight of 98 % or more | S | New | UNDER EXAMINATION | IT | Applicant | Round 2026/01: For use in the pharmaceutical industry |
| 2912 49 00 | | 1792518/2025 | 1005 | 5-(1,1-Dimethylethyl)-2-methoxybenzaldehyde (CAS RN 85943-26-6) with a purity by weight of 98 % or more | S | New | UNDER EXAMINATION | IT | Applicant | Round 2026/01: Used in the manufacture of pharmaceutical ingredients |
| 2914 50 00 | | 1939427/2025 | 1011 | 7-hydroxy-3,4-dihydronaphthalen-1(2H)-one (CAS RN 22009-38-7) with a purity by weight of 98 % or more | S | New | UNDER EXAMINATION | IT | Applicant | Round 2026/01: For use in the pharmaceutical |

| | | | | | | | | | | |
|------------|--|--------------|------|--|---|-----|-------------------|----|-----------|--|
| | | | | | | | | | | industry |
| 2916 14 00 | | 2278312/2025 | 1031 | 2-Hydroxyethyl methacrylate (CAS RN 868-77-9) with a purity by weight of 97 % or more | S | New | UNDER EXAMINATION | NL | Applicant | Round 2026/01: Used in the production of polymers |
| 2917 12 00 | | 2171718/2025 | 1026 | Bis(3,4-epoxycyclohexylmethyl)adipate (CAS RN 3130-19-6) of a purity by weight of 97 % or more | S | New | UNDER EXAMINATION | DE | Applicant | Round 2026/01: Used for coating, ink and composite applications |
| 2917 19 80 | | 2168744/2025 | 1025 | Dibutyl itaconate (CAS RN 2155-60-4) with a purity of 96 % by weight or more | S | New | UNDER EXAMINATION | NL | Applicant | Round 2026/01: Used in the production of coating resins |
| 2917 20 00 | | 2481545/2025 | 1033 | 1,2,3,6-Tetrahydrophthalic anhydride (CAS RN 85-43-8) with a purity by weight of 98 % or more | S | New | UNDER EXAMINATION | NL | Applicant | Round 2026/01: For use as an intermediate for polyesters, plasticizers, adhesives, and as a hardener for resins |
| 2918 29 00 | | 1898599/2025 | 1008 | 3-hydroxy-2-naphthoic acid (CAS RN 92-70-6) with a purity by weight of 99 % or more | S | New | UNDER EXAMINATION | ES | Applicant | Round 2026/01: Used in the pharmaceutical industry |
| 2918 30 00 | | 2272516/2025 | 1030 | 2-(4-Chlorobenzoyl)benzoic acid (CAS RN 85-56-3) with a purity by weight of 99 % or more | S | New | UNDER EXAMINATION | NL | Applicant | Round 2026/01: For use in the resins & polymer industry |
| 2918 30 00 | | 2204124/2025 | 1029 | Prohexadione-calcium (ISOM) (CAS RN 127277-53-6) with a purity by weight of 95 % or more | S | New | UNDER EXAMINATION | NL | Applicant | Round 2026/01: For use as plant growth regulator |
| 2918 99 90 | | 2366645/2025 | 1317 | methyl-3-methoxyacrylate with a purity by weight of 98 % or more CAS RN 5788-17-0 | S | New | UNDER EXAMINATION | FI | Applicant | Round 2026.1 to be used for the materials to produce crop protection products |

| | | | | | | | | | | |
|------------|--|--------------|------|--|---|-----|-------------------|-------|------------------------|--|
| 2918 99 90 | | 2171914/2025 | 1027 | 3,4-Epoxy cyclohexylmethyl-3',4'-epoxycyclohexane carboxylate (CAS RN 2386-87-0) of a purity by weight of 91 % or more | S | New | UNDER EXAMINATION | DE | Applicant | Round 2026/01: used for UV-curing coatings, inks and composite applications |
| 2920 29 00 | | 2312786/2025 | 1315 | Tris(2-chloroethyl) phosphite (CAS RN 140-08-9) with a purity by weight of 90 % or more | S | New | UNDER EXAMINATION | NL | Applicant | Round 2026.1 used as a flame retardant additive |
| 2922 29 00 | | 2065421/2025 | 1017 | 4-Amino-2,3-dichlorophenol (CAS RN 39183-17-0) with a purity by weight by 98 % or more | S | New | UNDER EXAMINATION | DE | Applicant | Round 2026/01: Used in the production of plant protection products |
| 2922 49 85 | | 2189820/2025 | 1028 | Magnesium;2-aminoacetate (CAS RN 14783-68-7) with a purity by weight of 100 %, imported in packages not less than 25Kg; not put up for retail sale | S | New | UNDER EXAMINATION | IE | Applicant | Round 2026/01: for use in the health food and supplement industry |
| 2923 10 00 | | 2029862/2025 | 1014 | Calcium Phosphoryl Choline Chloride (CAS RN 72556-74-2) with a purity by weight of 90 % or more | S | New | UNDER EXAMINATION | ES | Applicant | Round 2026/01: For use in the pharmaceutical industry |
| 2924 29 70 | | 1902090/2025 | 1009 | Calcium bis[(2r,4s)-5-(biphenyl-4-yl)-4-(3-carboxypropionylamino)-2-methylpentanonic acid ethyl ester)] salt with a purity by weight of 98,0 % or more | S | New | UNDER EXAMINATION | SI IE | Applicant Co-applicant | Round 2026/01: Used in the pharmaceutical industry |
| 2925 29 00 | | 2166771/2025 | 1023 | N-amidininosarcosine hydrate (CAS 6020-87-7) with a purity by weight of 99 % or more, imported in packages not less than 25 kg | S | New | UNDER EXAMINATION | IE | Applicant | Round 2026/01: For use in the health food and supplement industry |
| 2926 90 70 | | 1713491/2025 | 1003 | 2,3,3,3-Tetrafluoro-2-(trifluoromethyl)propanenitrile (CAS RN 42532-60-5) with a purity by weight of 99 % or more | S | New | UNDER EXAMINATION | FR | Applicant | Round 2026/01: used as inert gas for the insulation of high voltage installation |
| 2926 90 70 | | 1790113/2025 | 1004 | 3,4-dimethoxybicyclo[4.2.0]octa-1,3,5,-triene-7-carbonitrile (CAS RN 35202-54-1) | S | New | UNDER EXAMINATION | ES | Applicant | Round 2026/01: for use in the |

| | | | | | | | | | | |
|------------|--|--------------|------|---|---|-----|-------------------|----|-----------|---|
| | | | | with a purity by weight of 97 % or more | | | | | | pharmaceutical industry |
| 2931 90 00 | | 2163644/2025 | 1021 | F3 – Catalyst of an organic hafnium compound in powder form (CAS RN 264926-41-2) or dissolved in hexane (CAS RN 657-27-2) with a purity of 95 % or more | S | New | UNDER EXAMINATION | AT | Applicant | Round 2026/01: For use in the production of polyethylene |
| 2931 90 00 | | 2164499/2025 | 1022 | Hydrogen tetrakis(pentafluorophenyl)borate(1-)—N,N-dimethylaniline (1:1) (CAS RN 118612-00-3) with a purity by weight of 99 % or more | S | New | UNDER EXAMINATION | AT | Applicant | Round 2026/01: For use in the production of polyethylene |
| 2932 20 90 | | 2168134/2025 | 1024 | 6-Dimethylamino-3,3-bis(4-dimethylaminophenyl)phthalide (CAS RN 1552-42-7) with a purity by weight of 96 % or more | S | New | UNDER EXAMINATION | NL | Applicant | Round 2026/01: Used in the manufacturing of carbonless copy paper |
| 2933 39 99 | | 1793363/2025 | 1006 | (1R,2S,4R)-2-Benzhydrylquinuclidin-3-one (2R,3R)-2,3-dihydroxysuccinate (CAS RN 683206-54-4) with a purity by weight of 98 % or more | S | New | UNDER EXAMINATION | IT | Applicant | Round 2026/01: Used in the production of pharmaceutical ingredients |
| 2933 99 80 | | 1793936/2025 | 1007 | (2R,3R)-2-(2,4-Difluorophenyl)-1-(1H-1,2,4-triazol-1-yl)butane-2,3-diol methanesulfonate (CAS RN 1175536-50-1) with a purity by weight of 98 % or more | S | New | UNDER EXAMINATION | IT | Applicant | Round 2026/01: Used in the production of pharmaceutical ingredients |
| 2934 99 90 | | 2028227/2025 | 1013 | Disodium uridine-5'-monophosphate (CAS RN 3387-36-8) with a purity by weight of 98 % or more | S | New | UNDER EXAMINATION | ES | Applicant | Round 2026/01: For use in the manufacture of food supplement products |
| 2934 99 90 | | 2057866/2025 | 1016 | Nedosiran Sodium (CAS RN 2247026-22-6) with a purity by weight of 95 % or more | S | New | UNDER EXAMINATION | DK | Applicant | Round 2026/01: For use in the pharmaceutical industry |
| 2934 99 90 | | 1790941/2025 | 1001 | [6R-[6 α ,7 β (Z)]]-7-[2-furyl(methoxyimino)acetamido]-3- | S | New | UNDER EXAMINATION | IT | Applicant | Round 2026/01: used in the |

| | | | | | | | | | | |
|------------|--|--------------|------|--|---|-----|-------------------|----|-----------|---|
| | | | | (hydroxymethyl)-8-oxo-5-thia-1-azabicyclo[4.2.0]oct-2-ene-2-carboxylic acid (CAS RN 56271-94-4) with a purity by weight of 96 % or more | | | | | | manufacturing of antibiotics |
| 3808 99 90 | | 1697141/2025 | 1000 | Milbemycin oxime (CAS RN 129496-10-2), mixture of A3 (C31H43NO7) and A4 (C32H45NO7), predominantly A4, with a purity by weight of 95 % or more | S | New | UNDER EXAMINATION | FR | Applicant | Round 2026/01: Used for the manufacture of deworming for dogs and cats |
| 3812 10 00 | | 2486402/2025 | 1035 | TBSI - Rubber vulcanizing agent consisting of a light white to light yellow-brown powder, the product is a preparation, with the following components: - N-(1,1-dimethylethyl) bis(2-benzothiazolesulfen) amide (CAS RN 3741-80-8) with a purity by weight of 98 % or more and - White mineral oil (petroleum) (CAS RN 8042-47-5) with a purity by weight of 2 % or more | S | New | UNDER EXAMINATION | RO | Applicant | Round 2026/01: Used in the manufacture of tyres |
| 3824 99 92 | | 2483059/2025 | 1034 | Trimethylolpropane ethoxylate (CAS RN 50586-59-9) | S | New | UNDER EXAMINATION | NL | Applicant | Round 2026/01: Used in the production of polymers |
| 3824 99 92 | | 2279213/2025 | 1032 | Mixture of primary tert-alkylamines (CAS RN 68955-53-3) | S | New | UNDER EXAMINATION | DE | Applicant | Round 2026/01: For use in the production of phosphoric acid ester |
| 3824 99 92 | | 1903259/2025 | 1010 | Pentanoic acid, 5-(dimethylamino)-2-methyl-5-oxo-,methyl ester (CAS RN 1174627-68-9) with a purity by weight of 75 % or more | S | New | UNDER EXAMINATION | FR | Applicant | Round 2026/01: Used in the production of plant protection products |
| 3824 99 96 | | 2072871/2025 | 1018 | Yttria Stabilized Zirconia (YSZ) (CAS RN 64417-98-7) of a purity by Zirconia of 90 % or more | S | New | UNDER EXAMINATION | AT | Applicant | Round 2026/01: Used in the production of bioceramics, structural ceramics, |

| | | | | | | | | | | |
|------------|--|--------------|------|--|---|-----|-------------------|-------|-------------------|--|
| | | | | | | | | | | technical ceramics |
| 3901 10 10 | | 2246559/2025 | 1310 | Linear low-density polyethylene (ethylene-1-butene) (CAS RN 25087-34-7), - with a melt flow rate (MFR 190 °C/2.16 kg) of 0.43 or more but not more than 1.00 g/10 min, - with a density (ASTM D 1505) of 0.915 g/cm³ or more, but not more than 0.942 g/cm³. | S | New | UNDER EXAMINATION | TR | Applicant | Round 2026.1 to be used as a raw material for flexible packaging production |
| 3902 10 00 | | 2277892/2025 | 1313 | Polypropylene containing no plasticiser, - of a tensile strength: of 26 - 36 MPa (as determined by ISO 527 method), - of a melt Flow Rate (mfr) at 230 °C of 10 - 30 g/10 min (as determined by the ISO 1133 method), - of flexural modulus higher than 2300 MPa (as determined by the ISO 178 method), - with 60 % or more but not more 90 % by weight of Polypropylene, - with 10 % or more but not more than 45 % by weight of talc powder. - recycled material is above 99 % Polypropylene component coming from a single source of polypropylene recycled. | S | New | UNDER EXAMINATION | CZ | Applicant | Round 2026.1 to be used in assembling air conditioning units of vehicles |
| 3904 69 80 | | 2275570/2025 | 1312 | Polyvinylidene Difluoride (PVDF) (CAS RN 24937-79-9) | S | New | UNDER EXAMINATION | TR FR | Applicant Opposed | Round 2026.1 to be used in the production of capillary membrane (hollow fiber) |
| 3911 90 19 | | 2225697/2025 | 1306 | Benzenamine, 4,4'-oxybis-, polymer with 1,3-benzenediamine and 1,3-dihydro-1,3-dioxo-5-isobenzofurancarboxyl chloride (CAS RN | S | New | UNDER EXAMINATION | BE | Applicant | Round 2026.1 to be used in the production of protective and adhesive coatings |

| | | | | | | | | | | |
|------------|--|--------------|------|---|---|-----|-------------------|----|-----------|--|
| | | | | 35463-82-2) or 5-Isobenzofurancarboxyl chloride, 1,3-dihydro-1,3-dioxo-, polymer with 4,4'-methylenebis[benzenamine] (CAS RN 25928-85-2) containing by weight not more than 35 % of additives | | | | | | |
| 3911 90 99 | | 2205779/2025 | 1305 | A mixture containing by weight: - 89 % or more but not more than 91 % of 1,4:5,8- Dimethanonaphthalene, 2-ethylidene-1,2,3,4,4a,5,8,8a-octahydro-, polymer with 3a,4,7,7a- tetrahydro- 4,7-methano-1H-indene, hydrogenated (CAS RN 881025-72-5), and - 9 % or more but not more than 11 % of Polypropylene Homopolymer (CAS RN 9003-07-0) | S | New | UNDER EXAMINATION | IE | Applicant | Round 2026.1 for use in the production of disposable contact lenses |
| 3920 62 19 | | 2246820/2025 | 1311 | Reflecting polyester sheeting embossed in a pyramidal pattern, for the manufacture of safety stickers, badges and tapes, safety clothing and accessories thereof, or of school satchels, bags or similar containers | S | New | UNDER EXAMINATION | IE | Applicant | Round 2026.1 to be used in the production of reflective safety products usually under CN 39191080 and 39199080 |
| 3921 19 00 | | 2026850/2025 | 1302 | Strip of microporous polytetrafluoroethylene on a support of a non-woven for use in the manufacture of filters for kidney dialysis equipment (1) | S | New | UNDER EXAMINATION | IE | Applicant | Round 2026.1 for use in the production of medical equipment |
| 4016 99 57 | | 2246416/2025 | 1309 | Wiper rubber specifically designed for the manufacture of windshield wipers for motor vehicles under the tariff heading 8512 with; - a length of 300mm or more but not more than 700mm; - made of with NRCR 60 Shore A structure | S | New | UNDER EXAMINATION | TR | Applicant | Round 2026.1 to be used in vehicle wiper blades |

| | | | | | | | | | | |
|------------|--|--------------|------|---|---|-----|-------------------|----|-----------|--|
| 5402 33 00 | | 2204850/2025 | 1304 | Textured polyester yarn: - textured using single heater and double heater methods, - with a linear density of 83 dtex or more, but not more than 666 dtex, - with an average minimum tenacity of 32 cN/tex, - with a filament count of 36 or more, but not more than 192, - with an elongation of 16 % or more, but not more than 33 %, - with a boiling water shrinkage of 3 % or more, but not more than 8 %, - with a content of preparation 1 % or more, but not more than 3 % | S | New | UNDER EXAMINATION | PL | Applicant | |
| 5403 31 00 | | 1835626/2025 | 1301 | Viscose rayon filament yarn centrifugal, measuring 80 decitex or more, but not more than 88 decitex, consisting of a number of monofilaments of 24 or more, but not more than 36. | S | New | UNDER EXAMINATION | ES | Applicant | Round 2026.1 for the production of fabrics |
| 5602 10 19 | | 2281825/2025 | 1314 | Needle punched felt with a polyvinyl alcohol content of 20 % or more but not more than 40 % | S | New | UNDER EXAMINATION | TR | Applicant | Round 2026.1 to be used in the manufacture of microfiber synthetic leather |
| 5902 10 10 | | 2235613/2025 | 1307 | Cord fabric obtained by impregnating nylon or other polyamides with rubber containing by weight of: - 90 % or more but not more than 98 % Polyamide 6 - 2 % or more but not more than 7 % RFL (Resorcinol Formaldehyde Latex) and - 1 % or less cotton yarn for use in any type of transport vehicle tire | S | New | UNDER EXAMINATION | TR | Applicant | Round 2026.1 to be used in the production of vehicle tires |

| | | | | | | | | | | |
|------------|--|--------------|------|---|---|-----|-------------------|----|-----------|--|
| 7019 80 10 | | 2165498/2025 | 1303 | Vacuum Insulation Panel consisting of a hermetic casing made of multi-layer foil with aluminum surrounding a rigid core, devoid of air, used for thermal insulation of the interior of the fridge-freezer: - the main insulating material of the product is fiberglass (wool fiber) (min 70 %), - panel thickness 15 mm or more, but not more than 35 mm, - width 165 mm or more, but not more than 510 mm, - length 375 mm or more, but not more than 1875 mm, - thermal conductivity coefficient K-factor below 0.0015 kcal/(h·m·°C), - ambient temperature during operation from -50 °C or more, but not more than 80 °C | S | New | UNDER EXAMINATION | PL | Applicant | Round 2026.1 used in the production of refrigerators |
| 8109 29 00 | | 1835222/2025 | 1300 | Non-alloy zirconium sponges or ingots containing by weight more than 0,01 % of hafnium for use in the manufacture of tubes, bars or ingots enlarged by remelting for the non-nuclear industry (1) | S | New | UNDER EXAMINATION | SE | Applicant | Round 2026.1 for the production of bars and tubes used in non-nuclear industry |
| 8207 19 10 | | 2246032/2025 | 1308 | Inserts for drilling tools with working parts of agglomerated diamonds | S | New | UNDER EXAMINATION | TR | Applicant | Round 2026.1 to be used in PDC (Polycrystalline Diamond Compact) drill bits |
| 8409 91 00 | | 2947092/2025 | 2011 | Connecting rod for connecting pistons to the crankshaft of a passenger car engine: - made of an alloy containing 96 % steel and the remainder being titanium, vanadium, aluminum, chromium, nickel, copper, phosphorus, silicon, sulfur, | S | New | UNDER EXAMINATION | PL | Applicant | Round 01/2026 - new request component for the automotive industry |

| | | | | | | | | | | |
|------------|--|--------------|------|--|---|-----|-------------------|----|-----------|--|
| | | | | <p>manganese,</p> <ul style="list-style-type: none"> - with two connecting rod bolts, - with plain bearing, - of a length of 120 mm or more but not more than 160 mm, - with a surface roughness corresponding to ISO 4287-1997, <p>for use in the manufacture of motor vehicle engines (1)</p> | | | | | | |
| 8414 30 20 | | 2446092/2025 | 1323 | <p>Hermetic compressor for R600a refrigerant for the production of refrigerators and fridge-freezers:</p> <ul style="list-style-type: none"> - with a power not exceeding 0.4 KW, - pre-filled with mineral lubricant oil from 110 cm3 to 175 cm3, - suction and processing pipe inner diameter from 6.34 to 6.74 mm, thickness from 0.6 to 0.8 mm, - discharge pipe inner diameter from 4.9 to 5.1 mm, thickness from 0.75 to 0.95 mm, - hermetic clamp and bracket, which can be assembled with a plastic cover, - speed range from 900 rpm to 4500 rpm, - driven by a brushless DC electric motor, - cooling capacity from 76 to 110 W at 1800 rpm <p>(1)</p> | S | New | UNDER EXAMINATION | PL | Applicant | Round 2026.1 used in the production of refrigerators and fridge-freezers |
| 8414 59 25 | | 3032672/2025 | 2016 | <p>DC Brushless Axial Fan, to be used in instrument clusters, speedometers, multimedia and infotainment systems for transport vehicles, with:</p> <ul style="list-style-type: none"> - a rated voltage between: 3 to 16 VDC - an operating voltage between: 3 to 16 VDC - an rated current between: 0,03 to 0,30 | S | New | UNDER EXAMINATION | PT | Applicant | Round 01/2026 - new request component for the automotive industry |

| | | | | | | | | | | |
|------------|--|--------------|------|--|---|-----|-------------------|----|-----------|---|
| | | | | <p>A</p> <ul style="list-style-type: none"> - an input power between: 0,3 to 1,5 W - a rotation speed between: 2500 to 10000 R.P.M. - an air flow of not more than 25 CFM (cubic foot per minute) - an air pressure of not more than 10 mmH2O - an overall sound of not more than 45 dB(A) - a diameter of not more than 65mm <p>With or without an heat sink incorporated</p> | | | | | | |
| 8414 90 00 | | 2464396/2025 | 1324 | <p>Air conditioning compressor housing component made of aluminum alloy for installation in electric air conditioning compressors for motor vehicles:</p> <ul style="list-style-type: none"> - with a width of 100 mm or more but not more than 220 mm, - with a length of 100 mm or more but not more than 230 mm, - with a height of 80 mm or more but not more than 180 mm, - with one single central bore, - machined or unwrought, - whether or not impregnated, - with one suction port or without. | S | New | UNDER EXAMINATION | HU | Applicant | Round 2026.1 to be incorporated in electric air conditioning compressors for motor vehicles |
| 8418 99 90 | | 2705253/2025 | 2004 | <p>Evaporator, which is a type of heat exchanger used in refrigerators and refrigerators with freezers:</p> <ul style="list-style-type: none"> - with an external dimensions from 362x244x60mm to 398.4x503x60 mm, - with aluminium radiators with dimensions from 60x26.7 mm to 60.2x27.3 mm, - with an aluminium tube with an external diameter of 8.4 - 8.5 mm, - with a straight internal channel or with an elongated internal channel with grooves of 40 pcs grooves, | S | New | UNDER EXAMINATION | PL | Applicant | Round 01/2026 - new request component household appliance industry |

| | | | | | | | | | | |
|------------|--|--------------|------|--|---|-----|-------------------|----|-----------|--|
| | | | | <ul style="list-style-type: none"> - with 229 to 307 radiating fins, - without heaters or max. with two heaters with power of 40 W or more, but not more than 140 W, - without thermal fuses or with two such fuses with a melting point of 77 °C | | | | | | |
| 8418 99 90 | | 2727561/2025 | 2006 | <p>Condenser for a refrigerator, which is a heat exchanger, mounted on the back of refrigerators and fridge-freezers:</p> <ul style="list-style-type: none"> - a steel pipe with a diameter of 4.68-4.81 mm, a wall thickness of 0.52-0.65 mm, - 26-30 pcs of horizontal pipe sections, each straight with a length of 450-455 mm, spaced every 40 mm between each horizontal part, - having from 112 to 174 pcs welded steel rods with a diameter of 1.3 mm and a length of 1002-1322 mm, - having 3 clips, - having 4 brackets welded between the rods, - having an optional decorative cover made of black polyvinyl chloride, a length of 443 mm or more, but not more than 450 mm | S | New | UNDER EXAMINATION | PL | Applicant | Round 01/2026 - new request components for domestic appliance industry |
| 8481 80 99 | | 2400121/2025 | 1319 | <p>Service valve which suits for R410A or R32 gas while connecting indoor and outdoor units with:</p> <ul style="list-style-type: none"> - a withstanding pressure of the valve body of 6,3 MPa, - a leakage ratio of less than 1.6 g/a, - an impurity ratio of less than 1.2 mg/PCS, - an airtight pressure of the valve body of 4.2 Mpa <p>for use in the manufacture of air</p> | S | New | UNDER EXAMINATION | TR | Applicant | Round 2026.1 used as component in air conditioning systems |

| | | | | | | | | | | |
|------------|--|--------------|------|--|---|-----|-------------------|----|-----------|--|
| | | | | conditioners (1) | | | | | | |
| 8483 50 80 | | 2947464/2025 | 2012 | <p>Flywheel for damping torsional vibrations and oscillations within the car's drivetrain:</p> <ul style="list-style-type: none"> - with a total moment of inertia of 0.082 kg.m², - with a weight of 7 kg or more, but not more than 8 kg, - with a diameter of 250 mm or more, but not more than 280 mm <p>for use in the manufacture of motor vehicles(1)</p> | S | New | UNDER EXAMINATION | SK | Applicant | Round 01/2026 - new request component for the automotive industry |
| 8501 31 00 | | 2701255/2025 | 2002 | <p>DC motor, brushless, integrated with an Electronic Control Unit (ECU), defined as a Power Pack with:</p> <ul style="list-style-type: none"> - a safety feature and mechanism designed for prevention of critical hazards like self-steer by single failure, - a CAN-communication interface, - an external sensor interface, - operating temperature range of -40°C to 95°C or broader, - compliance with standard IP6K9K for water and dustproofness, - supply voltage of 9 V or more, but not more than 16 V, - rated power output of 500 W or more, but not higher than 750 W, - rated torque of 3 Nm or more, but not more than 6 Nm, - length of 150 mm or more, but not more than 250 mm, - width of 100 mm or more, but not more than 150 mm, - height of 80 mm or more, but not more than 120 mm | S | New | UNDER EXAMINATION | PL | Applicant | Round 01/2026 - new request components for the automotive industry |

| | | | | | | | | | | |
|------------|--|--------------|------|---|---|-----|-------------------|----|-----------|---|
| 8501 31 00 | | 2705655/2025 | 2005 | Brushless DC electric motor: <ul style="list-style-type: none"> - with an output power of 200 W or greater, but not exceeding 700 W, - with a supply voltage of 30 V or greater, but not exceeding 60 V, - with a torque of 30 Nm or greater, but not exceeding 200 Nm, - with an outer diameter of 135 mm or greater but not exceeding 175 mm, - with a weight of 2 kg or greater but not exceeding 5 kg, - designed to be mounted in a frame, front or rear bicycle wheel, - equipped with an LCD display | S | New | UNDER EXAMINATION | PL | Applicant | Round 01/2026 - new request component for the automotive industry |
| 8501 40 20 | | 2946361/2025 | 2010 | Single-phase brushless AC motor with an output not exceeding 750W, incomplete, for drum drive of washing machines and washer-dryers, consisting of rotor and stator: <ul style="list-style-type: none"> - rotor on the inside is equipped with a ring of 12 magnets housed in a steel casing, - stator with an internal diameter of 206.6 mm (± 0.5), external diameter of 265.0 mm (± 0.2) and width of 37.2 mm to 47.8 mm, - with a rated power not exceeding 750 W, - with a mass of 5 kg or more, used in the production of washing machines, washer-dryers equipped with a drum with direct drive | S | New | UNDER EXAMINATION | PL | Applicant | Round 01/2026 - new request component for the household appliances industry |
| 8507 60 00 | | 2730921/2025 | 2007 | Rechargeable lithium-ion batteries: <ul style="list-style-type: none"> - with fuse, - with a battery cell design, - using LFP technology, - with a length of 1055 mm or more, but not more than 1065 mm, | S | New | UNDER EXAMINATION | PL | Applicant | Round 01/2026 new request batteries/accumulators |

| | | | | | | | | | | |
|------------|--|--------------|------|---|---|-----|-------------------|----|-----------|--|
| | | | | <ul style="list-style-type: none"> - with a width of 630 mm or more, but not more than 640 mm, - of a height of 242 mm or more but not more than 253 mm, - of a mass of 262 kg or more but not more than 270 kg, - with a capacity of 268 Ah, - with upper outer casing made of composite material, - with IP68 protection level or more, - with energy density of 264 Wh/dm³ or higher, - with specific energy of 167 Wh/kg or higher, - without contactors, <p>for use in the manufacture of batteries for electric buses (1)</p> | | | | | | |
| 8507 60 00 | | 2479524/2025 | 1328 | <p>Lithium-ion rechargeable batteries with:</p> <ul style="list-style-type: none"> - a length of 700 mm or more, but not more than 2 820 mm, - a width of 935 mm or more, but not more than 1 660 mm, - a height of 85 mm or more, but not more than 700 mm, - a weight of 250 kg or more, but not more than 700 kg, - a power of not more than 175 kWh - a nominal voltage of 650V or more, but not more than 800V | S | New | UNDER EXAMINATION | ES | Applicant | Round 2026.1 to be used in electric vehicles |
| 8507 60 00 | | 2944920/2025 | 2009 | <p>Lithium Iron Phosphate (LFP) Blade Cell (in-line anode and cathode position to both ends of cell) with embedded anti-vibration bracket:</p> <ul style="list-style-type: none"> - with a length of 110 mm or more but not more than 145.5 mm, - with a width of 40 mm or more but not more than 58.2 mm, | S | New | UNDER EXAMINATION | TR | Applicant | Round 01/2026 - new request batteries/accumulators |

| | | | | | | | | | | |
|------------|--|--------------|------|--|---|-----|-------------------|----|-----------|--|
| | | | | <ul style="list-style-type: none"> - with a height of 401 mm or more but not more than 405.2 mm, - with a weight of 3500 gr (\pm %0,5) or more but not more than 7000 gr (\pm %0,5), - with a nominal Capacity of 150 Ah or more but not more than 300 Ah | | | | | | |
| 8507 60 00 | | 2478190/2025 | 1326 | <p>A rechargeable lithium-ion battery pack, based on lithium nickel manganese cobalt technology (NCM) with:</p> <ul style="list-style-type: none"> - a length of 2584 mm or more, but not exceeding 2856 mm, - a width of 1028 mm or more, but not exceeding 1132 mm, - a height of 160 mm or more, but not exceeding 181 mm, - a weight of 600 kg or more, but not exceeding 651 kg, - a power not exceeding of 115 kWh or more, but not exceeding 128 kWh, - a nominal capacity of 148 Ah or more, but not exceeding 174 Ah, - a nominal voltage of 718 V or more, but not exceeding 793 V. | S | New | UNDER EXAMINATION | BE | Applicant | Round 2026.1 for use in electric trucks |
| 8507 60 00 | | 2704328/2025 | 2003 | <p>A rechargeable lithium-ion battery, containing a fuse, in cell-to-pack design, with:</p> <ul style="list-style-type: none"> - a length of 1 050 mm or more, but not more than 1 070 mm, - a width of 624 mm or more, but not more than 636 mm, - a height of 235 mm or more, but not more than 245 mm, - a mass of 214,4 kg or more, but not more than 227,6 kg, - a capacity of 228 Ah, - using LFP technology, - an upper outer casing of the battery | S | New | UNDER EXAMINATION | PL | Applicant | Round 2026-01 new request battery industry |

| | | | | | | | | | | |
|------------|--|--------------|------|--|---|-----|-------------------|----|-----------|--|
| | | | | <p>made of a composite material,</p> <ul style="list-style-type: none"> - battery with R100.02 certificate, - protection class IP 68 (battery connected to the system), - without contactors, - with volumetric energy of 220Wh/l or higher, - gravimetric energy of 159Wh/kg or higher, <p>for use in the the manufacture of batteries for electric buses (1)</p> | | | | | | |
| 8507 60 00 | | 2733173/2025 | 2008 | <p>Rechargeable lithium-ion batteries:</p> <ul style="list-style-type: none"> - with fuse, - with a battery cell design, - using LFP technology, - with a length of 1345 mm or more, but not more than 1355 mm, - with a width of 655 mm or more, but not more than 665 mm, - with a height of 238 mm or more, but not more than 248 mm, - with a mass of 272 kg or more, but not more than 275 kg, - with a capacity of 95 Ah, - with upper outer casing made of composite material, - with IP68 protection level, or more, - with energy density of 135 Wh/dm³ or higher, - with specific energy of 112 Wh/kg or higher, - without contactors, <p>for use in the manufacture of batteries for electric buses (1)</p> | S | New | UNDER EXAMINATION | PL | Applicant | Round 01/2026 - new request batteries/accumulators |
| 8507 60 00 | | 2478851/2025 | 1327 | <p>A rechargeable lithium-ion battery pack, based on Lithium-iron-phosphate</p> | S | New | UNDER EXAMINATION | BE | Applicant | Round 2026.1 to be used in electric trucks |

| | | | | | | | | | | |
|------------|--|--------------|------|--|---|-----|-------------------|----|-----------|--|
| | | | | <p>technology (LFP) with:</p> <ul style="list-style-type: none"> - a length of 2613 mm or more, but not exceeding 2888 mm, - a width of 1026 mm or more, but not exceeding 1134 mm, - a height of 257 mm or more, but not exceeding 284 mm, - a weight of 1089 kg or more, but not exceeding 1203 kg, - a power of 170 or more, but not exceeding 182 kWh, - a nominal capacity of 215 or more, but not exceeding 245 Ah, - a nominal voltage of 729 or more, but not exceeding 805 V | | | | | | |
| 8507 60 00 | | 2477462/2025 | 1325 | <p>Cells for the manufacture of lithium-ion electric accumulators with:</p> <ul style="list-style-type: none"> - a length of 250 mm or more, but not more than 265 mm, - -a width of 22 mm or more, but not more than 26 mm, - -a height of 100 mm or more, but not more than 110 mm, - -a weight of 1,4 kg or more, but not more than 1,6 kg, - -a capacity of not more than 92 Ah and a nominal energy of less than 291 Wh | S | New | UNDER EXAMINATION | CZ | Applicant | Round 2026.1 to be used in the manufacture of accumulators for electric vehicles |
| 8512 20 00 | | 2443446/2025 | 1322 | <p>Sub-assembly reflectors and components for car rear lights:</p> <ul style="list-style-type: none"> - containing two or three PCBA with a connection socket and LED, - with central control module (CCE) connected through wired harness, - with a main reflector, a sub-reflector and inner lens scattering the light made of plastic, - with depth of 119 mm or more, but | S | New | UNDER EXAMINATION | PL | Applicant | Round 2026.1 to be used as component of lighting system of passenger vehicles |

| | | | | | | | | | | |
|------------|--|--------------|------|--|---|-----|-------------------|----|-----------|---|
| | | | | not more than 146 mm, - with width of 142 mm or more, but not more than 490 mm, - with a height of 93 mm or more, but not more than 100 mm, - a weight of 414 g or more, but not more than 578 g, - with lightguide | | | | | | |
| 8537 10 91 | | 2947957/2025 | 2013 | Control unit for the automatic transmission oil pump for efficient cooling and oil pressure regulation in the car's drivetrain: - liquid-cooled, - with an operating voltage of 9 V DC or more, but not more than 16 V, - with a height of 165 mm or more, but not more than 190 mm, - with a width of 40 mm, but not more than 60 mm, - with a length of 170 mm or more, but not more than 195 mm, - in a casing, - with one or more connectors, and for use in the manufacture of hybrid motor vehicles (1) | S | New | UNDER EXAMINATION | SK | Applicant | Round 01/2026 - new request component for the automotive industry |
| 8549 13 20 | | 2695775/2025 | 2000 | Spent lithium-ion or nickel metal hydride electric accumulators | S | New | UNDER EXAMINATION | BE | Applicant | round 01/2026 battery industry |
| 8708 50 99 | | 2948134/2025 | 2014 | Roll rod assembly for the front suspension in vehicles for connecting the stabilizer to the suspension components: - made of aluminum, rubber, and plastic, - with a height of 270 mm or more, but not more than 300 mm, - with a width of 50 mm, but not more than 65 mm, - with a length of 150 mm or more, but | S | New | UNDER EXAMINATION | SK | Applicant | Round 01/2026 - new request component for the automotive industry |

| | | | | | | | | | | |
|------------|--|--------------|------|--|---|-----|----------------------|----|-----------|---|
| | | | | not more than 170 mm, for use in the manufacture of motor vehicles (1) | | | | | | |
| 8708 95 99 | | 2948356/2025 | 2015 | The airbag assembly for enhancing safety in the event of a car collision: - with a wiring harness, - with a polyamide inflatable safety cushion, - with an inflator containing cold gas, - in a housing, - with mounting brackets for use in the manufacture of motor vehicles(1) | S | New | UNDER EXAMINATION | SK | Applicant | Round 01/2026 - New request component for the automotive industry |
| 8708 99 97 | | 2696943/2025 | 2001 | Mounting bracket of front radiator or intercooler whether or not with rubber cushioning for use in the manufacture of goods of Chapter 87 (1) | S | New | UNDER EXAMINATION | SK | Applicant | Round 01/2026 new request for components for the automotive industry |
| 8714 93 00 | | 2411868/2025 | 1321 | Gear set without a pawl mechanism, mounted on a hub drum, connecting sprockets: - with 7 row or more sprockets, but not more than 12 row sprockets, - with 10 teeth per gear or more, but not more than 52 teeth, - with a weight of 200 g or greater, but not exceeding 800 g, - with sprockets made of nickel-plated steel or aluminium for use in the manufacture of bicycles and e- bikes (1) | S | New | UNDER EXAMINATION | PL | Applicant | Round 2026.1 to be used in the production of bicycles and e-bikes |
| 9401 99 20 | | 3080179/2025 | 2017 | Cassette, a locking mechanism mounted on the seat skeleton, designed for use in the manufacture of passenger car seats | S | New | UNDER EXAMINATION | TR | Applicant | Round 01/2026 - new request component for the automotive industry |

| | | | | | | | | | | |
|---------------|----|--|------|--|---|-----------|-------------------|-------|-------------------|--|
| ex 2823 00 00 | 10 | 294577/2011 446/2/1995 PROLONG 2023 | 5105 | Titanium dioxide (CAS RN 13463-67-7): - of a purity by weight of 99,9 % or more, - with an average grain-size of 0,7 µm or more but not more than 2,1 µm | S | Amendment | UNDER EXAMINATION | AT EU | Applicant Opposed | Round 2026-01 - review of the measure, |
| ex 2827 39 85 | 10 | 1255/2/1992 PROLONG 2019 PROLONG 2024 PROLONG 2025 | 5111 | DE new proposal: Copper monochloride of a purity by weight of 96 % or more (CAS RN 7758-89-6) --- Current description: Copper monochloride (CAS RN 7758-89-6) of a purity by weight of 96 % or more but not more than 99 % | S | Amendment | UNDER EXAMINATION | IT | Applicant | Round 2026-01 - request for amendment.// |
| ex 2903 99 80 | 80 | 311432/2013 PROLONG 2019 PROLONG 2024 PROLONG 2025 | 5112 | DE new proposal: 1-Bromo-3,4,5-trifluorobenzene (CAS RN 138526-69-9) with a purity by weight of 99 % or more --- Current description: 1-Bromo-3,4,5-trifluorobenzene (CAS RN 138526-69-9) | S | Amendment | UNDER EXAMINATION | DE | Applicant | Round 2026-01 request for amendment.// |
| ex 2905 22 00 | 20 | 5450710/2016 PROLONG 2022 | 5113 | DE new proposal: 3,7-Dimethyloct-6-en-1-ol (CAS RN 106-22-9) with a purity by weight of 94 % or more --- Current description: 3,7-Dimethyloct-6-en-1-ol (CAS RN 106-22-9) | S | Amendment | UNDER EXAMINATION | DE | Applicant | Round 2026-01 - request for amendment.// |
| ex 2907 12 00 | 30 | 3078811/2014 PROLONG 2020 PROLONG 2025 | 5114 | DE new proposal: p-Cresol (CAS RN 106-44-5) with a purity by weight of 99 % or more | S | Amendment | UNDER EXAMINATION | DE | Applicant | Round 2026-01 - request for amendment.// |

| | | | | | | | | | | |
|---------------|----|---|------|--|---|-----------|----------------------|----|-----------|--|
| | | | | *** Current text: p-Cresol (CAS RN 106-44-5) | | | | | | |
| ex 2907 19 10 | 10 | 555815/2014 PROLONG 2020 PROLONG 2025 | 5119 | DE new proposal: 2,6-Xylenol (CAS RN 576-26-1) with a purity by weight of 99 % or more *** Current description: 2,6-Xylenol (CAS RN 576-26-1) | S | Amendment | UNDER EXAMINATION | DE | Applicant | Round 2026-01 - request for amendment.// |
| ex 2907 29 00 | 70 | 1747/1/2002 PROLONG 2019 PROLONG 2024 PROLONG 2025 | 5115 | DE new proposal: 2,2',2'',6,6',6''-Hexa-tert-butyl- α,α',α'' - (mesitylen-2,4,6-triyl)tri-p-kresol (CAS RN 1709-70-2) with a purity by weight of 98 % or more --- Current test: 2,2',2'',6,6',6''-Hexa-tert-butyl- α,α',α'' - (mesitylene-2,4,6-triyl)tri-p-cresol (CAS RN 1709-70-2) | S | Amendment | UNDER EXAMINATION | IT | Applicant | Round 2026-01 request for amendment.// |
| ex 2907 29 00 | 75 | 4509689/2017 PROLONG 2019 PROLONG 2024 PROLONG 2025 | 5116 | DE new proposal: Biphenyl-4,4'-diol (CAS RN 92-88-6) with a purity by weight of 99 % or more --- Current text: Biphenyl-4,4'-diol (CAS RN 92-88-6) | S | Amendment | UNDER EXAMINATION | DE | Applicant | Round 2026-01 request for amendment.// |
| ex 2909 30 90 | 30 | 598074/2010 PROLONG 2016 PROLONG 2021 | 5117 | DE new proposal: 3,4,5-Trimethoxytoluene (CAS RN 6443- 69-2) with a purity by weight of 98 % or more --- Current text: 3,4,5-Trimethoxytoluene (CAS RN 6443- 69-2) | S | Amendment | UNDER EXAMINATION | DE | Applicant | Round 2026-01 request for amendment.// |

| | | | | | | | | | | |
|---------------|----|--|------|--|---|-----------|----------------------|----------|---------------------------|--|
| ex 2916 39 90 | 70 | 1728/1/2002 PROLONG 2019 PROLONG 2024 PROLONG 2025 | 5104 | DE new proposal: Ibuprofen (INN) (CAS RN 15687-27-1) with a purity by weight of 99 % or more *** Current text: Ibuprofen (INN) (CAS RN 15687-27-1) | S | Amendment | UNDER EXAMINATION | BE DE | Applicant Co-applicant | Round 2026-01 - request for amendment. |
| ex 2919 90 00 | 25 | 1605700/2019 PROLONG 2025 | 5020 | Triphenyl phosphate (CAS RN 115-86-6) | S | Amendment | UNDER EXAMINATION | IT EU | Applicant Opposed | Round 2026-01 - objection.// |
| ex 2921 42 00 | 55 | 1692715/2019 PROLONG 2025 | 5118 | DE new proposal: 4-chloroaniline (CAS RN 106-47-8) with a purity by weight of 99 % or more --- Current text: 4-Chloroaniline (CAS RN 106-47-8) | S | Amendment | UNDER EXAMINATION | ES | Applicant | Round 2026-01 request for amendment.// |
| ex 2922 19 00 | 35 | 3962047/2015 PROLONG 2021 | 5103 | DE: 2- [2- (dimethylamino) ethoxy] ethanol (CAS RN 1704-62-7) with a purity by weight of 98 % or more *** Current text: 2-[2-(Dimethylamino)ethoxy] ethanol (CAS RN 1704-62-7) | S | Amendment | UNDER EXAMINATION | DE DE | Applicant Co-applicant | Round 2026-01 - Prolongation Exercise |
| ex 2930 90 95 | 53 | 1091197/2015 PROLONG 2021 | 5120 | DE new proposal: Bis(4-chlorophenyl) sulphone (CAS RN 80- 07-9) with a purity by weight of 98 % or more --- Current description: Bis(4-chlorophenyl) sulphone (CAS RN 80- 07-9) | S | Amendment | UNDER EXAMINATION | DE | Applicant | Round 2026-01 - request for amendment.// |

| | | | | | | | | | | |
|---------------|----|--|------|---|---|-----------|----------------------|----------------|---|--|
| ex 2933 19 90 | 25 | 662163/2014 PROLONG 2020 PROLONG 2025 | 5110 | DE new proposal: 3-Difluoromethyl-1-methyl-1H-pyrazole-4- carboxylic acid (CAS RN 176969-34-9) with a purity by weight of 97 % or more --- Current description: 3-Difluoromethyl-1-methyl-1H-pyrazole-4- carboxylic acid (CAS RN 176969-34-9) | S | Amendment | UNDER EXAMINATION | DE | Applicant | Round 2026-01 request for amendment.// |
| ex 2933 39 99 | 21 | 3081637/2014 PROLONG 2020 PROLONG 2025 | 5223 | DE new peoposal: Boscalid (ISO) (CAS RN 188425-85-6) with a purity by weight of 98 % or more --- Current description: Boscalid (ISO) (CAS RN 188425-85-6) | S | Amendment | UNDER EXAMINATION | DE | Applicant | Round 2026-01 - request for amendment.// |
| ex 2933 49 10 | 10 | 457/5/1998 PROLONG 2019 PROLONG 2024 PROLONG 2025 | 5121 | DE: Quinmerac (ISO) (CAS RN 90717-03-6) with a purity by weight of 98 % or more *** Current description: Quinmerac (ISO) (CAS RN 90717-03-6) | S | Amendment | UNDER EXAMINATION | DE | Applicant | Round 2026-01 - request for amendment.// |
| ex 2933 99 80 | 20 | 1412/2/1990 PROLONG 2019 PROLONG 2024 PROLONG 2025 | 5122 | DE new proposal: 2-(2H-Benzotriazol-2-yl)-4,6-bis(1-methyl- 1-phenylethyl)phenol (CAS RN 70321-86- 7) with a purity by weight of 99 % or more *** Current description: 2-(2H-Benzotriazol-2-yl)-4,6-bis(1-methyl- 1-phenylethyl)phenol (CAS RN 70321-86- 7) | S | Amendment | UNDER EXAMINATION | DE | Applicant | Prolongation Exercise |
| ex 2934 99 90 | 58 | 1687/6/1996 PROLONG 2019 | 5102 | DE new proposal: Dimethenamide-P (ISO) (CAS RN 163515- 14-8) with a purity by weight of 93 % or | S | Amendment | UNDER EXAMINATION | DE BE FR | Applicant Co-applicant Co-applicant | Prolongation exercise |

| | | | | | | | | | | |
|---------------|----|---|------|--|---|-----------|----------------------|----------|---------------------------|---|
| | | PROLONG 2024 PROLONG 2025 | | more ** Current text: Dimethenamide-P (ISO) (CAS RN 163515-14-8) | | | | | | |
| ex 3204 17 00 | 48 | 384794/2013 994086/2011 PROLONG 2019 | 5141 | Preparation, in the form of extruded beads, containing by weight: - 60 % or more but not more than 70 % of Colourant C.I. Pigment Yellow 174 (CAS RN 78952-72-4), - 30 % or more, but not more than 40 % disproportionated rosin (CAS RN 8050-09-7), - whether or not containing kaolin | S | Amendment | UNDER EXAMINATION | NL BE | Applicant Co-applicant | Round 2026-01 to be deleted, newly accepted product will cover this one./ |
| ex 3206 11 00 | 10 | 1887/16/2002 PROLONG 2019 PROLONG 2024 PROLONG 2025 | 5106 | Titanium dioxide coated with isopropoxytitanium triisostearate, containing by weight 1,5 % or more but not more than 2,5 % of isopropoxytitanium triisostearate | S | Amendment | UNDER EXAMINATION | FR EU | Applicant Opposed | Round 2026-01 - review of the measure |
| ex 3215 90 70 | 40 | 577797/2010 PROLONG 2016 PROLONG 2021 | 5321 | Dry ink powder with a base of hybrid resin (made from polystyrene acrylic resin and polyester resin) mixed with: - wax - a vinyl-based polymer and - a colouring agent for use in the manufacture of toner bottles for photocopiers, fax machines, printers and multifunction devices (2) | S | Amendment | UNDER EXAMINATION | FR | Applicant | Round 2026-01 - amendment |
| ex 3824 99 92 | 43 | 1605793/2019 PROLONG 2025 | 5021 | Preparation containing by weight: - 65 % or more, but not more than 95 % of isopropylated triaryl phosphate (CAS RN 68937-41-7) and | S | Amendment | UNDER EXAMINATION | IT EU | Applicant Opposed | Round 2026-01 - objection./ |

| | | | | | | | | | | |
|---------------|----|---------------------------------------|------|---|---|-----------|-------------------|----------|-----------------------------|--|
| | | | | - 5 % or more, but not more than 35 % of triphenyl phosphate (CAS RN 115-86-6) | | | | | | |
| ex 3824 99 92 | 69 | 1102055/2015 PROLONG 2022 | 5022 | Preparation containing by weight: - 80 % or more but not more than 92 % of Bisphenol-A bis(diphenyl phosphate) (CAS RN 5945-33-5) - 7 % or more but not more than 20 % oligomers of Bisphenol-A bis(diphenyl phosphate) and - not more than 1 % triphenyl phosphate (CAS RN 115-86-6) | S | Amendment | UNDER EXAMINATION | FR NL EU | Applicant Applicant Opposed | Round 2026-01 - objection.// |
| ex 3824 99 92 | 74 | 6480217/2022 | 5023 | Reaction mass containing by weight: - 22,4 % or more, but not more than 26,4 % of 3-methylphenyl diphenyl phosphate (CAS RN 69500-28-3); - 17,3 % or more, but not more than 21,3 % of 4-methylphenyl diphenyl phosphate (CAS RN 78-31-9); - 5 % or more, but not more than 9 % of bis(3-methylphenyl) phenyl phosphate (CAS RN 34909-68-7); - 8,9 % or more, but not more than 12,9 % of 3-methylphenyl 4-methylphenyl phenyl phosphate (CAS RN 222165-66-4); - 26,9 % or more, but not more than 30,9 % of triphenyl phosphate (CAS RN 115-86-6) | S | Amendment | UNDER EXAMINATION | IT EU | Applicant Opposed | Round 2026-01 - objection Component flame retardant |
| ex 3905 99 90 | 97 | 1728/7/2002 PROLONG 2019 PROLONG 2024 | 5108 | DE new proposal: Povidone-iodine (CAS RN 25655-41-8) with a purity by weight of 92 % or more *** Current text: Povidone (INN)-iodine (CAS RN 25655- | S | Amendment | UNDER EXAMINATION | BE | Applicant | Round 2026-01 - Request for amendment.// |

| | | | | | | | | | | |
|---------------|----|--------------|------|---|---|-----------|-------------------|----|-----------|--|
| | | | | 41-8) | | | | | | |
| ex 3911 90 19 | 15 | 1889490/2021 | 5109 | <p>NL new proposal: Polyetherimide of</p> <ul style="list-style-type: none"> - 5,5'-[(isopropylidene)bis(4,1-phenylene)dioxy]bis(1,3-isobenzofurandione) and 1,3-benzenediamine whether or not with 3-aminopropyl terminated dimethylsilicones or dimethylsiloxanes (CAS RN 61128-46-9 and 99904-16-2), or - 5,5'-[(isopropylidene)bis(4,1-phenylene)dioxy]bis(1,3-isobenzofurandione) and 1,4-benzenediamine (CAS RN 61128-47-0), or - 5,5'-[(isopropylidene)bis(4,1-phenylene)dioxy]bis(1,3-isobenzofurandione) and 4,4'-sulfonylbis(benzenamine) (CAS RN 77699-82-2), or - 4,4'-[(isopropylidene)bis(4,1-phenylene)dioxy]bis(1,3-isobenzofurandione), 5,5'-[(isopropylidene)bis(4,1-phenylene)dioxy]bis(1,3-isobenzofurandione), 4,5'-[(isopropylidene)bis(4,1-phenylene)dioxy]bis(1,3-isobenzofurandione), pyromellitic dianhydride, 1,2-benzenediamine, 1,3-benzenediamine and 1,4-benzenediamine with phthalic anhydride endcaps (CAS RN 96557-46-9), or - 4,4'-[(isopropylidene)bis(4,1-phenylene)dioxy]bis(1,3-isobenzofurandione) and 4,4'-sulfonylbis(benzenamine) (CAS RN 1234673-19-8), or | S | Amendment | UNDER EXAMINATION | NL | Applicant | Round 2026-01 - request for amendment.// |

| | | | | | | | | | | |
|---------------|----|---------------------------------|------|--|---|-----------|----------------------|----------------|---------------------------------|---|
| | | | | <p>- 4,4'-[(isopropylidene)bis(4,1-phenylene)dioxy]bis(1,3-isobenzofurandione) and 4,4'-(9H-fluoren-9-ylidene)bis[benzenamine] with phthalic anhydride endcaps (CAS RN 2803979-49-7)</p> <p>----</p> <p>Current text: Polyetherimide of 4,4'-[(isopropylidene)bis(p-phenylenoxy)]diphthalic dianhydride and 1,3-benzenediamine or 1,4-benzenediamine (CAS RN 61128-46-9 or CAS RN 61128-47-0)</p> | | | | | | |
| ex 3920 99 28 | 50 | 3423/06 PROLONG 2022 | 5101 | <p>DE new proposal: Thermoplastic polyurethane film, of a thickness of 20 µm or more but not more than 450 µm, covered on one side with a removable protective film</p> <p>***</p> <p>Current text: Thermoplastic polyurethane film, of a thickness of 250 µm or more but not more than 350 µm, covered on one side with a removable protective film</p> | S | Amendment | UNDER EXAMINATION | BE BE DE | Applicant Opposed Opposed | Round 2026-01 - objection. |
| ex 3921 19 00 | 60 | 1575341/2017 PROLONG 2023 | 5129 | <p>Multi-porous multilayer separator foil with:</p> <ul style="list-style-type: none"> - one microporous polyethylene layer between two microporous polypropylene layers and whether or not containing a coating of aluminium oxide on both sides, - a width of 65 mm or more but not more than 170 mm, - a total thickness of 0,01 mm or more but not more than 0,03 mm, | S | Amendment | UNDER EXAMINATION | HU | Applicant | Round 2025-01 - review of the suspension + request change in classification, from CN 39211900 to CN 85079031.// |

| | | | | | | | | | | |
|---------------|----|----------------|------|---|---|-----------|-------------------|----|-----------|--|
| | | | | - a porosity of 0,25 or more but not more than 0,65 | | | | | | |
| ex 7019 80 10 | 30 | 6663116/2024-1 | 5231 | <p>PL new proposal: Vacuum insulation panel, consisting of a gas-tight aluminum foil housing surrounding a rigid, air-free core with:</p> <ul style="list-style-type: none"> - a glass wool filling, - a thickness of 5,6 mm or more but not more than 32,4 mm, - a length of 195 mm or more but not more than 1 835 mm, - a width of 155 mm or more but not more than 545 mm, - a thermal conductivity lower than or equal to 2,5 mW/mK, - an internal pressure below 1,0 Pa, - an ambient temperature during operation of -50 °C or more but not more than 80 °C <p>---</p> <p>Current description: Vacuum insulation panel, consisting of a gas-tight aluminum foil housing surrounding a rigid, air-free core with:</p> <ul style="list-style-type: none"> - a glass wool filling, - a thickness of 5,6 mm or more but not more than 32,4 mm, - a length of 195 mm or more but not more than 1 835 mm, - a width of 155 mm or more but not more than 545 mm, - a thermal conductivity lower than 2,5 mW/mK, - an internal pressure of 0,1 Pa, - an ambient temperature during operation of -50 °C or more but not more than 70 °C | S | Amendment | UNDER EXAMINATION | PL | Applicant | Round 2026-01 request for amendment.// |

| | | | | | | | | | | |
|---------------|----|----------------|------|---|---|-----------|-------------------|----|-----------|---|
| ex 7019 90 00 | 60 | 6663116/2024-2 | 5444 | <p>PL new proposal: Vacuum insulation panel, consisting of a gas-tight aluminum foil housing surrounding a rigid, air-free core with:</p> <ul style="list-style-type: none"> - a glass fiber filling, - a thickness of 5,6 mm or more but not more than 32,4 mm, - a length of 195 mm or more but not more than 1 835 mm, - a width of 155 mm or more but not more than 545 mm, - a thermal conductivity lower than or equal to 2,5 mW/mK, - an internal pressure below 1,0 Pa, - an ambient temperature during operation of -50 °C or more but not more than 80 °C <p>***</p> <p>Current description: Vacuum insulation panel, consisting of a gas-tight aluminum foil housing surrounding a rigid, air-free core with:</p> <ul style="list-style-type: none"> - a glass fiber filling, - a thickness of 5,6 mm or more but not more than 32,4 mm, - a length of 195 mm or more but not more than 1 835 mm, - a width of 155 mm or more but not more than 545 mm, - a thermal conductivity lower than 2,5 mW/mK, - an internal pressure of 0,1 Pa, - an ambient temperature during operation of -50 °C or more but not more than 70 °C | S | Amendment | UNDER EXAMINATION | PL | Applicant | Round 2026-01 request for amendment.// Round 2025/7 used for production of refrigerators, freezers and fridge-freezers |
| ex 8419 50 80 | 30 | 2132672/2024 | 5125 | <p>SK new proposal: Aluminium heat exchanger for gas boilers designed for heat transfer:</p> <ul style="list-style-type: none"> - with a height of 100 mm or more, but | S | Amendment | UNDER EXAMINATION | SK | Applicant | Round 2026-01 - request for amendment.// Round 2025/01 |

| | | | | | | | | | | |
|---------------|----|--------------|------|--|---|------------------|-------------------|----|-----------|---|
| | | | | <p>not more than 150 mm,</p> <ul style="list-style-type: none"> - with a width of 235 mm, but not more than 300 mm, - with a length of 240 mm or more, but not more than 300 mm, - for a power output of 25 kW or more, but not more than 35 kW, - with a weight of 8 kg or more, but not more than 10 kg <p>---</p> <p>Current description: Aluminium heat exchanger for gas boilers designed for heat transfer:</p> <ul style="list-style-type: none"> - with a height of 100 mm or more, but not more than 120 mm, - with a width of 235 mm, but not more than 280 mm, - with a length of 250 mm or more, but not more than 280 mm, - for a power output of 25 kW or more, but not more than 35 kW, - with a weight of 8 kg or more, but not more than 10 kg | | | | | | Components for the energy industry. |
| ex 8483 50 80 | 20 | 4997528/2020 | 5224 | <p>HU new proposal: Pulley blocks of non-cast steel:</p> <ul style="list-style-type: none"> - made of structural carbon steel complying with standard JIS G4051, - with an external diameter of 104mm or more but not more than 142mm, - with an internal diameter of 33mm or more but not more than 37mm, - with a width of 22mm or more but not more than 40mm, - with a weight of 0,4kg or more but not more than 1,6kg, - with 4 trapezoidal grooves or more but not more than 7 | S | Amendment | UNDER EXAMINATION | HU | Applicant | Round 2026-01: request for amendment + prolongation item.// |

| | | | | | | | | | | |
|--------------------------------|----------|---------------------------------|------|--|---|------------------|----------------------|----|-----------|--|
| | | | | <p>---</p> <p>Current description:</p> <p>Pulley blocks of non-cast steel:</p> <ul style="list-style-type: none"> - made of structural carbon steel complying with standard JIS G4051, - with an external diameter of 104 mm or more but not more than 142 mm, - with an internal diameter of 33 mm or more but not more than 37 mm, - with a width of 22 mm or more but not more than 40 mm, - with a weight of 0,4 kg or more but not more than 1,6 kg, - with 6 trapezoidal grooves | | | | | | |
| ex 8544 30 00 ex 8544 42 90 | 60 50 | 1233371/2015 PROLONG 2021 | 5123 | <p>SK new proposal:</p> <p>Four-core connecting cable containing two female connectors for the transmission of digital signals from navigation and/or audio systems to a USB connector and/or LCD monitor, for use in the manufacture of goods of Chapter 87</p> <p>---</p> <p>Current description:</p> <p>Four-core connecting cable containing two female connectors for the transmission of digital signals from navigation and audio systems to a USB connector, for use in the manufacture of goods of Chapter 87 (2)</p> | S | Amendment | UNDER EXAMINATION | SK | Applicant | Round 2026-01 - Request for amendment.// |
| ex 8708 40 20 ex 8708 40 50 | 70 60 | 5776455/2019 PROLONG 2025 | 5124 | <p>SK new proposal:</p> <p>Manual gearbox in cast aluminium housing for transverse installation with:</p> <ul style="list-style-type: none"> - a width of not more than 550 mm, - a height of not more than 500 mm, - a length of not more than 600 mm, - five or six gears, - a differential gear, - an engine torque of 400 Nm or less, <p>for use in the manufacture of motor vehicles</p> | S | Amendment | UNDER EXAMINATION | CZ | Applicant | Round 2026-01 - request for amendment.// |

| | | | | | | | | | | |
|---------------|----|--------------|------|---|---|-----------|-------------------|----|-----------|--|
| | | | | <p>of Heading 8703</p> <p>---</p> <p>Current description: Manual gearbox in cast aluminium housing for transverse installation with:</p> <ul style="list-style-type: none"> - a width of not more than 480 mm, - a height of not more than 400 mm, - a length of not more than 550 mm, - five or six gears, - a differential gear, - an engine torque of 400 Nm or less, <p>for use in the manufacture of motor vehicles of Heading 8703 (2)</p> | | | | | | |
| ex 8708 40 20 | 80 | 5701899/2021 | 5131 | <p>CZ new proposal: Transmission gearbox without torque converter, with:</p> <ul style="list-style-type: none"> - -dual clutch, - -7 or more forward gears, - -1 reverse gear, - -a maximum torque of 450 Nm, - -whether or not with electric motor integrated, - -a height of 350 mm or more but not more than 600 mm, - -a width 350 mm or more but not more than 600 mm, and - a weight of 70 kg or more but not more than 110 kg, <p>for use in the manufacture of motor vehicles of Heading 8703</p> <p>---</p> <p>Current description: Transmission gearbox without torque converter, with:</p> <ul style="list-style-type: none"> - dual clutch, - 7 or more forward gears, - 1 reverse gear, | S | Amendment | UNDER EXAMINATION | SE | Applicant | Round 2026-01 - request for amendment.// |

| | | | | | | | | | | |
|---------------|----|--------------|------|--|---|-----------|-------------------|----|-----------|--|
| | | | | <ul style="list-style-type: none"> - a maximum torque of 390 Nm, - whether or not with electric motor integrated, - a height of 400 mm or more but not more than 600 mm, - a width 350 mm or more but not more than 600 mm, and - a weight of 70 kg or more but not more than 110 kg, <p>for use in the manufacture of motor vehicles of Heading 8703 (2)</p> | | | | | | |
| ex 8708 40 50 | 25 | 6502103/2024 | 5227 | <p>TR new proposal: Transmission assembly housing 3 other shafts inside it and offering a rotating switch for shift position, consisting of:</p> <ul style="list-style-type: none"> - cast aluminium body, - differential gear, - 2 electrical motors and gears, - a width of 280 mm or more but no more than 470 mm, - a height of 350 mm or more but no more than 595 mm, - a length of 410 mm or more but no more than 690 mm, <p>for use in the manufacture of motor vehicles of subheadings 8703 40 and 8703 60</p> <p>---</p> <p>Current description: Transmission assembly housing 3 other shafts inside it and offering a rotating switch for shift position, consisting of:</p> <ul style="list-style-type: none"> - cast aluminium body, - differential gear, - 2 electrical machines and gears, - a width of 280 mm or more but no more than 470 mm, - a height of 350 mm or more but no | S | Amendment | UNDER EXAMINATION | TR | Applicant | Round 2026-01 request for amendment.// |

| | | | | | | | | | | |
|---|-----------------------|---|-------------|--|----------|-------------------------|-------------------------------|-----------|------------------|---|
| | | | | <p>more than 595 mm, - a length of 410 mm or more but no more than 690 mm, for use in the manufacture of motor vehicles of subheadings 8703 40 and 8703 60 (2)</p> | | | | | | |
| <p>ex 8708 50 20 ex 8708 50 99</p> | <p>75 35</p> | <p>4702919/2018 PROLONG 2024 PROLONG 2025</p> | <p>5333</p> | <p>PL new proposal: Constant velocity joint assembly for transmitting a torque from engine and transmission to wheels of motor vehicles, consisting of: - an inner race with 6 ball tracks or more but not more than 8 for running with the bearing balls with a diameter of 13,0 mm or more but not more than 28,0 mm, - an outer race with 6 ball tracks or more but not more than 8 for running with the bearing balls, made of steel with carbon content of 0,45 % or more but not more than 0,58 %, with thread and with a spline with 22 teeth or more but not more than 44, - a spherical cage keeping bearing balls in the ball tracks of outer race and inner race in proper angular position, made of material suitable for carburizing with carbon content of 0,14 % or more but not more than 0,55 %, and - with a grease compartment, - capable of working at constant speed at variable articulation angle not higher than 52 degrees</p> <p>---</p> <p>Current description: Outboard joint assembly for transmitting a torque from engine and transmission to wheels of motor vehicles, consisting of: - an inner race with 6 ball tracks for</p> | <p>S</p> | <p>Amendment</p> | <p>UNDER EXAMINATION</p> | <p>PL</p> | <p>Applicant</p> | <p>Round 2026-01 - request for amendment.//</p> |

| | | | | | | | | | | |
|--|--|--|--|---|--|--|--|--|--|--|
| | | | | <p>running with the bearing balls with a diameter 15,0 mm or more but not more than 20,0 mm,</p> <ul style="list-style-type: none"> - an outer race with 6 ball tracks for running with 6 bearing balls, made of steel with carbon content of 0,45 % or more but not more than 0,58 %, with thread and with a spline with 26 teeth or more but not more than 38, - a spherical cage keeping bearing balls in the ball tracks of outer race and inner race in proper angular position, made of material suitable for carburizing with carbon content of 0,14 % or more but not more than 0,25 %, and - with a grease compartment, <p>capable of working at constant speed at variable articulation angle not higher than 50 degrees</p> | | | | | | |
|--|--|--|--|---|--|--|--|--|--|--|

| Battery Related Suspensions for review in Round 2026-01 | | | | | | | | | | |
|---|-------|----------------|----------------|---|---|--------------------------|-------------------|----------------------------|--|--|
| CN code | TARIC | Reference Mail | Working Number | Description | S | New or amendment request | Measure status | Partner Position Country | Partner Position | Public Comments |
| ex 2825 20 00 | 10 | 6011549/2019 | 0900 | Lithium hydroxide monohydrate (CAS RN 1310-66-3) | S | Amendment | UNDER EXAMINATION | SE BE EU EU EU | Applicant Co-applicant Opposed Opposed Opposed | Round 2026/1 review |
| ex 2826 90 80 | 30 | 5899336/2021 | 0901 | Lithium hexafluorophosphate (CAS RN 21324-40-3) with a purity by weight of 99 % or more | S | Amendment | UNDER EXAMINATION | HU EU EU EU | Applicant Opposed Opposed Opposed | Round 2026-01 - review of the suspension |

| | | | | | | | | | | |
|---------------|----|--------------|------|---|---|-----------|-------------------|----------------------------|---|---|
| ex 2917 19 80 | 55 | 5953671/2021 | 0902 | Maleic acid (CAS RN 110-16-7) with a purity by weight of 99 % or more | S | Amendment | UNDER EXAMINATION | HU EU EU EU | Applicant Opposed Opposed Opposed | Round 2026-01 - review of the suspension |
| ex 2920 90 10 | 15 | 1432061/2018 | 0903 | Ethyl methyl carbonate (CAS RN 623-53-0) | S | Amendment | UNDER EXAMINATION | CZ EU EU EU | Applicant Opposed Opposed Opposed | Round 2026-01 - review of the suspension |
| ex 2920 90 10 | 23 | 6580292/2023 | 0904 | 1,3,2-Dioxathiolane 2,2-dioxide (CAS RN 1072-53-3) with a purity by weight of 99 %, or more | S | Amendment | UNDER EXAMINATION | HU EU EU | Applicant Opposed Opposed | Round 2026-01 - review of the suspension |
| ex 2920 90 10 | 45 | 5899366/2021 | 0905 | Ethylene carbonate (CAS RN 96-49-1) with a purity by weight of 99 % or more | S | Amendment | UNDER EXAMINATION | HU EU EU EU EU | Applicant Opposed Opposed Opposed Opposed | Round 2026-01 - review of the suspension |
| ex 2920 90 10 | 55 | 5899407/2021 | 0906 | Vinylene carbonate (CAS RN 872-36-6) with a purity by weight of 99,9 % or more | S | Amendment | UNDER EXAMINATION | HU EU EU EU EU | Applicant Opposed Opposed Opposed Opposed | Round 2026-01 - review of the suspension.// |
| ex 2920 90 10 | 65 | 5899447/2021 | 0907 | Vinyl ethylene carbonate (CAS RN 4427-96-7) with a purity by weight of 99 % or more | S | Amendment | UNDER EXAMINATION | HU EU EU EU EU | Applicant Opposed Opposed Opposed Opposed | Round 2026-01 - review of the suspension.// |
| ex 2920 90 10 | 85 | 6705077/2022 | 0908 | Diethyl carbonate (CAS RN 105-58-8) with a purity by weight of 99,9 % or more | S | Amendment | UNDER EXAMINATION | HU EU EU EU | Applicant Opposed Opposed Opposed | Round 2026-01 - review of the suspension.// |
| ex 3824 99 92 | 22 | 1957046/2022 | 0909 | Solution containing: - 30 % or more but not more than | S | Amendment | UNDER EXAMINATION | CZ EU | Applicant Opposed | Round 2026-01 - review of the |

| | | | | | | | | | | |
|-----------------------------|----|--------------|------|---|---|-----------|-------------------|----------------------|--|--|
| | | | | 40 % by weight of lithium hexafluorophosphate (CAS RN 21324-40-3), and - 60 % or more but not more than 70 % by weight of ethyl methyl carbonate (CAS RN 623-53-0), or dimethyl carbonate (CAS RN 616-38-6) | | | | EU | Opposed | suspension |
| ex 3824 99 92 | 52 | 1697432/2019 | 0910 | Electrolyte containing: - 5 % or more but not more than 20 % lithium hexafluorophosphate (CAS RN 21324-40-3) or lithium tetrafluoroborate (CAS RN 14283-07-9), - 60 % or more but not more than 90 % of a mixture of ethylene carbonate (CAS RN 96-49-1), dimethyl carbonate (CAS RN 616-38-6) and/or ethyl methyl carbonate (CAS RN 623-53-0), - 0,5 % or more but not more than 20 % 1,3,2-dioxathiolane 2,2-dioxide (CAS RN 1072-53-3), for use in the manufacture of motor vehicle batteries (1) | S | Amendment | UNDER EXAMINATION | PL EU EU EU | Applicant Opposed Opposed Opposed | Round 2026-01 - review of the suspension |
| ex 3824 99 92 | 71 | 6597948/2023 | 0911 | Mixture containing by weight: - 49 % or more but not more than 51 % of ethylene carbonate (CAS RN 96-49-1), and - 49 % or more but not more than 51 % of 1,3-propanesultone (CAS RN 1120-71-4) | S | Amendment | UNDER EXAMINATION | HU EU EU | Applicant Opposed Opposed | Round 2026/01 - review of the measure. |
| ex 3921 19 00 8507 90 31 | 40 | 3938612/2015 | 0912 | Transparent, microporous, acrylic acid grafted polyethylene film, in the form of rolls, with: | S | Amendment | UNDER EXAMINATION | FR EU | Applicant Opposed | Round 2025-01 - review of the suspension + request |

| | | | | | | | | | | |
|-----------------------------|----|--------------|------|---|---|-----------|-------------------|-------------|--|--|
| | | | | <ul style="list-style-type: none"> - a width of 98 mm or more but not more than 170 mm, - a thickness of 15 µm or more but not more than 36 µm, of a kind used for the manufacture of alkaline battery separators | | | | | | change in classification, from CN 39211900 to CN 85079031.// |
| ex 3921 19 00 8507 90 31 | 45 | 1489232/2017 | 0913 | <p>Microporous monolayer film of polypropylene or a microporous trilayer film of polypropylene, polyethylene and polypropylene, each film with:</p> <ul style="list-style-type: none"> - zero transversal production direction (TD) shrinkage, - a total thickness of 8 µm or more, but not more than 50 µm, - a width of 15 mm or more, but not more than 900 mm, - a length of more than 200 m, but not more than 8 000 m, - an average pore size between 0,02 µm and 0,1 µm, - laminated or not with a Polypropylene non-woven mat of 50 to 200 µm thickness, - coated or not with surfactant, - coated or not on 1 or 2 sides with a ceramic layer of min 1 µm thickness or more, but not more than 5 µm, - coated or not on 1 or 2 sides with a sticky binder, PVdF type or similar of min 0,5 µm thickness or more, but not more than 5 µm | S | Amendment | UNDER EXAMINATION | DE EU | Applicant Opposed | <p>Round 2025-01 - review of the suspension + request change in classification, from CN 39211900 to CN 85079031.//</p> <p>Round 2025-01 - review of the suspension</p> <p>Round 2024-01 - review of the suspension</p> <p>Round 2023-01 - review of the suspension</p> <p>Round 2022-01: Review of the measure.</p> <p>Round 2021-01: Amendment. 3.2% duty installed.Old Taric code 39211900 (80), new TARIC code 39211900(45).</p> <p>ROUND 2018-01 Zink-Luft-Knopfzellen, Lithium-Ion Zellen</p> |
| ex 8507 60 00 | 15 | 1144451/2015 | 0914 | <p>Cylindrical lithium-ion-accumulators or modules with:</p> <ul style="list-style-type: none"> - a nominal capacity of 8,8 Ah or more, but not more than 18 Ah, - a nominal voltage of 36 V or more, but not more than 48 V, - a power of 300 Wh or more, but | S | Amendment | UNDER EXAMINATION | AT NL EU EU | Applicant Co-applicant Opposed Opposed | Round 2026-01 - review of the suspension.// |

| | | | | | | | | | | |
|---------------|----|--------------|------|--|---|-----------|----------------------|----------------|---------------------------------|---|
| | | | | not more than 648 Wh, for use in the manufacture of electric bicycles (1) | | | | | | |
| ex 8507 60 00 | 18 | 4793865/2018 | 0915 | Lithium-ion polymer accumulator pack equipped with a battery management system and can-bus interface with: - 6 modules with 90 cells or more but not more than 192 cells, - a nominal voltage of 280 V or more but not more than 400 V, - a nominal capacity of 9,7 Ah or more but not more than 120 Ah, - a charging voltage of 110 V or more but not more than 495 V, and in a metal casing with: - a length of not more than 1 723 mm, - a width of not more than 1 162,23 mm, - a height of not more than 395 mm, for use in the manufacture of vehicle capable of being charged by plugging to external source of electric power of heading 8703 (1) | S | Amendment | UNDER EXAMINATION | SE EU | Applicant Opposed | Round 2026-01 - review of the suspension.// |
| ex 8507 60 00 | 21 | 2037672/2023 | 0916 | Cylindrical rechargeable lithium-ion polymer accumulator module with: - a cable, - a connector, - 1 or 2 cells, - a charge control module or NTC temperature sensor, - a fuse, - a weight of 37,3 g or more but not more than 91,5 g, - a nominal voltage of 3,2 V, - a battery capacity of 1 100 mAh or more but not more than 2 200 mAh, | S | Amendment | UNDER EXAMINATION | HU EU EU | Applicant Opposed Opposed | Round 2026-01 - review of the suspension.// |

| | | | | | | | | | | |
|---------------|----|--------------|------|--|---|-----------|-------------------|----------------------|--|---|
| | | | | for the manufacture of automatic emergency call devices for passenger cars (1) | | | | | | |
| ex 8507 60 00 | 24 | 2102065/2023 | 0917 | Rechargeable lithium-ion battery, based on lithium-iron-phosphate technology, with: <ul style="list-style-type: none"> - a fuse, - a cell-to-pack design, - a length of 985 mm or more but not more than 1 015 mm, - a width of 1 050 mm or more but not more than 1 070 mm - a height of 145 mm or more but not more than 160 mm, - a weight of 220 kg or more but not more than 250 kg, - a capacity of 200 Ah or more, - a specific energy density of 130 Wh/kg or more, for use in the manufacture of vehicles of subheading 8702 40 (1) | S | Amendment | UNDER EXAMINATION | NL EU EU | Applicant Opposed Opposed | Round 2026-01 - review of the suspension.// |
| ex 8507 60 00 | 26 | 6609698/2023 | 0918 | Modules for the assembly of electric accumulators using lithium ferrophosphate technology (LFP) with: <ul style="list-style-type: none"> - a length of 670 mm or more, but not more than 882 mm, - a width of 390 mm or more, but not more than 655 mm, - a height of 110 mm or more, but not more than 137 mm, - a weight of 60 kg or more, but not more than 165 kg, and - a power of 11 300 Wh or more, but not more than 29 360 Wh | S | Amendment | UNDER EXAMINATION | DE EU EU EU | Applicant Opposed Opposed Opposed | Round 2026/01 review of the measure.// |
| ex 8507 60 00 | 28 | 6598010/2023 | 0919 | HU new proposal: Lithium-ion rechargeable battery cell with: | S | Amendment | UNDER EXAMINATION | SK EU | Applicant Opposed | Round 2026-01 - review of the measure + request for |

| | | | | | | | | | | |
|---------------|----|--------------|------|---|---|-----------|-------------------|----------------|---------------------------------|---|
| | | | | <ul style="list-style-type: none"> - a length of 190 mm or more but not more than 380 mm, - a width of 90 mm or more but not more than 150 mm, - a height of 4 mm or more but not more than 35 mm, - a weight of 0,1 kg or more but not more than 2,5 kg, - a nominal voltage of 3,0 VDC or more but not more than 5,0 VDC, - a nominal capacity of not more than 150 Ah, <p>for use in the manufacture of rechargeable hybrid and electric vehicle batteries</p> <p>***</p> <p>Current description: Lithium-ion rechargeable battery cell with:</p> <ul style="list-style-type: none"> - a length of 190 mm or more but not more than 380 mm, - a width of 90 mm or more but not more than 150 mm, - a height of 4 mm or more but not more than 15 mm, - a weight of 0,1 kg or more but not more than 1,2 kg, - a nominal voltage of 3,0 VDC or more but not more than 4,0 VDC, - a nominal capacity of not more than 90 Ah, <p>for use in the manufacture of rechargeable hybrid and electric vehicle batteries (1)</p> | | | | | | amendment.// |
| ex 8507 60 00 | 29 | 1961285/2022 | 0920 | Lithium-ion rechargeable battery pack in a specific housing, suitable for use in digital still cameras, having: | S | Amendment | UNDER EXAMINATION | DE EU EU | Applicant Opposed Opposed | Round 2026-01 - review of the suspension.// |

| | | | | | | | | | | |
|---------------|----|--|------|---|---|-----------|----------------------|----------------------------|---|---|
| | | | | <ul style="list-style-type: none"> - a length of 50 mm or more, but not more than 120 mm, - a width of 35 mm or more, but not more than 80 mm, - a height of 15 mm or more, but not more than 45 mm, - a weight of 0,040 kg or more but not more than 0,085 kg; and - a capacity of not more than 2200 mAh | | | | EU EU | Opposed Opposed | |
| ex 8507 60 00 | 30 | 1572/14/1995 PROLONG 2015 PROLONG 2023 | 0921 | Cylindrical lithium-ion accumulator or module, with a length of 63 mm or more and a diameter of 17,2 mm or more, having a nominal capacity of 1 200 mAh or more, for use in the manufacture of rechargeable batteries (1) | S | Amendment | UNDER EXAMINATION | IE EU EU EU | Applicant Opposed Opposed Opposed | Round 2026-01 - review of the suspension |
| ex 8507 60 00 | 33 | 1232310/2015 | 0922 | Lithium-ion battery module or accumulator, with: <ul style="list-style-type: none"> - a length of 150 mm or more, but not more than 1 310 mm, - a width of 100 mm or more, but not more than 1 000 mm, - a height of 200 mm or more, but not more than 1 500 mm, - a weight of 50 kg or more, but not more than 200 kg, - cells of a nominal capacity of 58 Ah or more but not more than 500Ah, - a nominal output voltage of 230 V AC or 45 V or more but not more than 980 V DC | S | Amendment | UNDER EXAMINATION | NL EU EU EU EU | Applicant Opposed Opposed Opposed Opposed | Round 2026-01:review of the suspension.// |
| ex 8507 60 00 | 36 | 6609601/2023 | 0923 | Lithium-ion accumulator, with <ul style="list-style-type: none"> - multiple connected lithium-ion accumulator cells, - charging and monitoring electronics, | S | Amendment | UNDER EXAMINATION | DE EU EU | Applicant Opposed Opposed | Round 2026-01 review of the suspension.// |

| | | | | | | | | | | |
|---------------|----|--------------|------|--|---|-----------|-------------------|--|--|---|
| | | | | <ul style="list-style-type: none"> - a power of 74 Wh or more, but not more than 75 Wh, - in a plastic housing with electrical connection contacts and LCD display, for use in the manufacture of cordless vacuum cleaners or rechargeable power sources therefor (1) | | | | | | |
| ex 8507 60 00 | 38 | 323555/2012 | 0924 | Modules for the assembly of lithium-ion battery packs, with: <ul style="list-style-type: none"> - a length of 298 mm or more, but not more than 500 mm, - a width of 33,5 mm or more, but not more than 209 mm, - a height of 75 mm or more, but not more than 228 mm, - a weight of 3,6 kg or more, but not more than 17 kg, - a power of 458 Wh or more, but not more than 3 510 Wh, and - a voltage of less than 45 V or more than 70 V | S | Amendment | UNDER EXAMINATION | FR DE SE EU EU EU EU PL | Applicant Co-applicant Co-applicant Opposed Opposed Opposed Opposed Opposed | Round 2026-01 - review of the suspension.// |
| ex 8507 60 00 | 48 | 4922932/2020 | 0925 | Integrated battery system in a metal or plastic case with or without holders, consisting of: <ul style="list-style-type: none"> - a lithium-ion battery with a voltage of 36 V or more but not more than 50,4 V and a nominal energy between 0,3kWh and 0,9 kWh, - a Battery Management System, - a power relay, - a cooling system, - one to four connectors, for use in the manufacture of Mild-hybrid (mHEV) motor vehicles (1) | S | Amendment | UNDER EXAMINATION | CZ EU EU EU EU | Applicant Opposed Opposed Opposed Opposed | Round 2026-01 - review of the suspension. |
| ex 8507 60 00 | 58 | 4697852/2018 | 0926 | Prismatic lithium-ion electric accumulator with: | S | Amendment | UNDER EXAMINATION | PL DE | Applicant Co-applicant | Round 2026-01 - review of the |

| | | | | | | | | | | |
|---------------|----|--------------|------|---|---|-----------|-------------------|----------------------------|--|--|
| | | | | <ul style="list-style-type: none"> - a width of 120,0 mm or more but not more than 305,0 mm, - a thickness of 12,0 mm or more but not more than 67,0 mm, - a height of 72,0 mm or more but not more than 126,0 mm, - a nominal voltage of 3,6 V or more but not more than 3,75 V, and - a nominal capacity of 6,9 Ah or more not more than 265 Ah, for use in the manufacture of rechargeable electric vehicle batteries (1) | | | | EU EU EU EU | Opposed Opposed Opposed Opposed | suspension Round 2025-01 - review of the suspension |
| ex 8507 60 00 | 68 | 5988869/2019 | 0927 | Lithium-ion accumulator in a metal housing, with <ul style="list-style-type: none"> - a length of 65 mm or more, but not more than 225 mm, - a width of 10 mm or more, but not more than 75 mm, - a height of 60 mm or more, but not more than 285 mm, - a nominal voltage of 2,1 V or more, but not more than 3,8 V, and - a nominal capacity of 2,5 Ah or more, but not more than 325 Ah | S | Amendment | UNDER EXAMINATION | DE EU EU EU EU | Applicant Opposed Opposed Opposed Opposed | Round 2026-01 - review of the suspension |
| ex 8507 60 00 | 77 | 1095345/2012 | 0928 | Lithium-ion rechargeable batteries, with: <ul style="list-style-type: none"> - a length of 700 mm or more, but not more than 2 820 mm, - a width of 935 mm or more, but not more than 1 660 mm, - a height of 85 mm or more, but not more than 700 mm, - a weight of 250 kg or more, but not more than 700 kg, - a power of not more than 175 kWh, - a nominal voltage of 320 V or more, but not more than 430 V | S | Amendment | UNDER EXAMINATION | NL ES EU EU EU | Applicant Co-applicant Opposed Opposed Opposed | Round 2026-01 - review of the suspension.// |

| | | | | | | | | | | |
|---------------|----|--------------|------|---|---|-----------|-------------------|----------------------------------|--|---|
| ex 8507 60 00 | 83 | 5691842/2021 | 0929 | Modules for the assembly of lithium-ion electric accumulators with: - a length of 570 mm or more, but not more than 610 mm, - a width of 210 mm or more, but not more than 240 mm, - a height of 100 mm or more, but not more than 125 mm, - a weight of 28 kg or more, but not more than 35 kg, and - a capacity of not more than 2500 Ah and a nominal energy of less than 8,4 kW, for use in the manufacture of vehicles of subheadings 8703 60, 8703 70, 8703 80 and 8704 60 (1) | S | Amendment | UNDER EXAMINATION | DE EU EU EU | Applicant Opposed Opposed Opposed | Round 2026-01 - review of the suspension |
| ex 8507 90 80 | 55 | 2207294/2022 | 0930 | Top cap or housing made of aluminium or ferrous alloy or stainless steel: - whether or not including parts made of aluminum and aluminium alloy, - with or without sealing elements or other elements made of polymer material, - with or without a "current interrupt device " and an "evacuation valve" - with or without plastic sockets - with an outer diameter of 17 mm or more, but not more than 18 mm, or rectangular with: - length not greater than 450 mm, - width not greater than 200 mm, and - hight not greater than 150 mm, for use in the manufacture of lithium-ion batteries (1) | S | Amendment | UNDER EXAMINATION | DE TR EU EU EU EU | Applicant Applicant Opposed Opposed Opposed Opposed | Round 2026-01 - review of the suspension.// |
| ex 8536 41 90 | 60 | 1398260/2024 | 0931 | Power relay with the function of safely connecting or disconnecting the charging | S | Amendment | UNDER EXAMINATION | SK EU | Applicant Opposed | Round 2026/1 Review of the suspension.// |

| | | | | | | | | | | |
|--|--|--|--|--|--|--|--|--|--|--|
| | | | | and/or power circuit of 48V batteries in a plastic housing, containing: <ul style="list-style-type: none">- current sensor 50A/400V,- high voltage MILD fuse 70V/300A,- whether or not cable with connector, for use in the production of rechargeable batteries for hybrid and electric vehicles (1) | | | | | | |
|--|--|--|--|--|--|--|--|--|--|--|

(1) Suspension of duties is subject to end-use customs supervision in accordance with Article 254 of Regulation (EU) No 952/2013.'



2024/3213

19.12.2024

COUNCIL REGULATION (EU) 2024/3213

of 16 December 2024

amending Regulation (EU) 2021/2283 opening and providing for the management of autonomous tariff quotas of the Union for certain agricultural and industrial products

THE COUNCIL OF THE EUROPEAN UNION,

Having regard to the Treaty on the Functioning of the European Union, and in particular Article 31 thereof,

Having regard to the proposal from the European Commission,

Whereas:

- (1) In order to ensure a sufficient supply of certain agricultural and industrial products which are produced in insufficient quantities in the Union and thereby avoid any disturbances on the market for those products, autonomous tariff quotas of the Union ('quotas') were opened by Council Regulation (EU) 2021/2283 ⁽¹⁾. Within those quotas, products can be imported into the Union at reduced or zero duty rates.
- (2) As it is in the Union's interest to ensure an adequate supply of certain industrial products, and having regard to the fact that identical, equivalent or substitute products are not produced in sufficient quantities within the Union, it is necessary to open new quotas with order numbers 09.2540, 09.2541, 09.2542, 09.2543 at zero duty rates and 09.2795 at reduced duty rate for appropriate quantities of those products.
- (3) As the scope of the quotas with order numbers 09.2652 and 09.2927 has become inadequate to fulfil the needs of economic operators in the Union, the description of the products covered by those quotas should be amended. Additionally, the indication of the applicable TARIC code for the quota with order number 09.2652 should be amended. Furthermore, it is in the Union's interest to maintain the quota with order number 09.2652 solely for the purpose of using the products concerned in the manufacture of specific goods produced within the Union. The application of the quota with order number 09.2652 should therefore be made conditional on the specific use of the products concerned in accordance with Article 254 of Regulation (EU) No 952/2013 of the European Parliament and of the Council ⁽²⁾.
- (4) For the quotas with order numbers 09.2596, 09.2597 and 09.2685, the classification of those products in Annex I to Council Regulation (EEC) No 2658/87 (the 'Combined Nomenclature') ⁽³⁾ has changed. Therefore, the applicable Combined Nomenclature codes for those quotas should be amended.
- (5) As it is in the Union's interest to ensure an adequate supply of a certain industrial product, the volume of the quota with order number 09.2662 should be increased.
- (6) As the Union production capacity for a certain industrial product has been increased, the volume of the quota with order number 09.2679 should be decreased.
- (7) For the quotas with order numbers 09.2544, 09.2545, 09.2546, 09.2547, 09.2548, 09.2549, 09.2550, 09.2551, 09.2552, 09.2553, 09.2554, 09.2555, 09.2556, 09.2557, 09.2559 and 09.2560, the quota periods should be extended and the quota volumes should be adapted on a yearly basis, as the quotas were opened for a period of 6 months only and it is still in the Union's interest to maintain those quotas.
- (8) For the quota with order number 09.2808, the quota should be opened for a period of 6 months only in order to take into account the potential evolution of the production of those products in the Union.
- (9) For the quotas with order numbers 09.2563 and 09.2925, the quotas should be opened for a period of 6 months only in order to ensure that their continued existence does not conflict with any other Union policy. Additionally, it is in the Union's interest to reduce the volume of those quotas by half and to maintain those quotas solely for the purpose of using the products concerned in the manufacture of specific goods produced within the Union. The application of those quotas should therefore be made conditional on the specific use of the products concerned in accordance with Article 254 of Regulation (EU) No 952/2013.

⁽¹⁾ Council Regulation (EU) 2021/2283 of 20 December 2021 opening and providing for the management of autonomous tariff quotas of the Union for certain agricultural and industrial products, and repealing Regulation (EU) No 1388/2013 (OJ L 458, 22.12.2021, p. 33, ELI: <http://data.europa.eu/eli/reg/2021/2283/oj>).

⁽²⁾ Regulation (EU) No 952/2013 of the European Parliament and of the Council of 9 October 2013 laying down the Union Customs Code (OJ L 269, 10.10.2013, p. 1, ELI: <http://data.europa.eu/eli/reg/2013/952/oj>).

⁽³⁾ Council Regulation (EEC) No 2658/87 of 23 July 1987 on the tariff and statistical nomenclature and on the Common Customs Tariff (OJ L 256, 7.9.1987, p. 1, ELI: <http://data.europa.eu/eli/reg/1987/2658/oj>).

- (10) As it is no longer in the Union's interest to maintain the quotas with order numbers 09.2664, 09.2682 and 09.2926, those quotas should be closed with effect from 1 January 2025.
- (11) Taking into account the amendments to be made and for the sake of clarity, the Annex to Regulation (EU) 2021/2283 should be replaced.
- (12) Regulation (EU) 2021/2283 should therefore be amended accordingly.
- (13) In order to avoid any interruption in the application of the quota scheme and to comply with the guidelines set out in the communication from the Commission of 13 December 2011 concerning autonomous tariff suspensions and quotas, the changes provided for in this Regulation regarding the quotas for the products concerned should apply from 1 January 2025. This Regulation should therefore enter into force as a matter of urgency,

HAS ADOPTED THIS REGULATION:

Article 1

The Annex to Regulation (EU) 2021/2283 is replaced by the text set out in the Annex to this Regulation.

Article 2

This Regulation shall enter into force on the day following that of its publication in the *Official Journal of the European Union*.

It shall apply from 1 January 2025.

This Regulation shall be binding in its entirety and directly applicable in all Member States.

Done at Brussels, 16 December 2024.

For the Council

The President

K. KALLAS

ANNEX

‘ANNEX

| Order number | CN code | TARIC | Description | Quota period | Quota volume | Quota duty rate |
|--------------|--|--|---|--------------|----------------|-----------------|
| 09.2849 | ex 0710 80 69 | 10 | Mushrooms of the species <i>Auricularia polytricha</i> (uncooked or cooked by steaming or boiling), frozen, for the manufacture of prepared meals ⁽¹⁾ ⁽²⁾ | 1.1.-31.12. | 700 tonnes | 0 % |
| 09.2925 | ex 2309 90 31 ex 2309 90 31 ex 2309 90 96 ex 2309 90 96 | 51 59 51 59 | Feed additive, consisting on dry weight basis of: — 68 % or more, but not more than 80 % of L-lysine sulphate, and — not more than 32 % of other components such as carbohydrates and other amino acids, for use in the production of animal feed and/or for use in the production of pharmaceuticals ⁽¹⁾ | 1.1.-30.6. | 50 000 tonnes | 0 % |
| 09.2913 | ex 2401 10 35 ex 2401 10 70 ex 2401 10 95 ex 2401 10 95 ex 2401 10 95 ex 2401 20 35 ex 2401 20 70 ex 2401 20 95 ex 2401 20 95 ex 2401 20 95 | 91 10 11 21 91 91 10 11 21 91 | Natural unmanufactured tobacco, whether or not cut in regular size, having a custom value of not less than EUR 450 per 100 kg net weight, for use as binder or wrapper for the manufacture of goods falling within subheading 2402 10 00 ⁽¹⁾ | 1.1.-31.12. | 3 000 tonnes | 0 % |
| 09.2828 | 2712 20 90 | | Paraffin wax containing by weight less than 0,75 % of oil | 1.1.-31.12. | 180 000 tonnes | 0 % |

| Order number | CN code | TARIC | Description | Quota period | Quota volume | Quota duty rate |
|--------------|---------------|-------|---|--------------|----------------------|-----------------|
| 09.2600 | ex 2712 90 39 | 10 | Slack wax (CAS RN 64742-61-6) | 1.1.-31.12. | 100 000 tonnes | 0 % |
| 09.2578 | ex 2811 19 80 | 50 | Sulphamidic acid (CAS RN 5329-14-6) with a purity by weight of 95 % or more, whether or not with not more than 5 % addition of the anti-caking agent silicon dioxide (CAS RN 112926-00-8) | 1.1.-31.12. | 27 000 tonnes | 0 % |
| 09.2928 | ex 2811 22 00 | 40 | Silica filler in the form of granules, with a purity by weight of 97 % or more of silicon dioxide | 1.1.-31.12. | 1 700 tonnes | 0 % |
| 09.2806 | ex 2825 90 40 | 30 | Tungsten trioxide, including blue tungsten oxide (CAS RN 1314-35-8 or CAS RN 39318-18-8) | 1.1.-31.12. | 12 000 tonnes | 0 % |
| 09.2819 | ex 2833 25 00 | 30 | Copper hydroxide sulfate ($\text{Cu}_4(\text{OH})_6(\text{SO}_4)$), hydrate (CAS RN 12527-76-3) with a purity by weight of 98 % or more | 1.1.-31.12. | 240 000 kilograms | 0 % |
| 09.2872 | ex 2833 29 80 | 40 | Caesium sulphate (CAS RN 10294-54-9) in solid form or as aqueous solution containing by weight 48 % or more but not more than 52 % of caesium sulphate | 1.1.-31.12. | 400 tonnes | 0 % |
| 09.2567 | ex 2903 22 00 | 10 | Trichloroethylene (CAS RN 79-01-6) with a purity by weight of 99 % or more | 1.1.-31.12. | 11 885 000 kilograms | 0 % |
| 09.2837 | ex 2903 79 30 | 20 | Bromochloromethane (CAS RN 74-97-5) | 1.1.-31.12. | 600 tonnes | 0 % |
| 09.2933 | ex 2903 99 80 | 30 | 1,3-Dichlorobenzene (CAS RN 541-73-1) | 1.1.-31.12. | 2 600 tonnes | 0 % |
| 09.2700 | ex 2905 12 00 | 10 | Propan-1-ol (propyl alcohol) (CAS RN 71-23-8) | 1.1.-31.12. | 15 000 tonnes | 0 % |
| 09.2551 | ex 2905 29 90 | 40 | Prop-2-yn-1-ol (CAS RN 107-19-7) with a purity by weight of 99 % or more | 1.1.-31.12. | 150 tonnes | 0 % |
| 09.2830 | ex 2906 19 00 | 40 | Cyclopropylmethanol (CAS RN 2516-33-8) | 1.1.-31.12. | 20 tonnes | 0 % |
| 09.2851 | ex 2907 12 00 | 10 | O-cresol (CAS RN 95-48-7) having a purity of not less than 98,5 % by weight | 1.1.-31.12. | 20 000 tonnes | 0 % |

| Order number | CN code | TARIC | Description | Quota period | Quota volume | Quota duty rate |
|--------------|---------------|-------|---|--------------|------------------|-----------------|
| 09.2704 | ex 2909 49 80 | 20 | 2,2,2',2'-Tetrakis(hydroxymethyl)- 3,3'-oxydipropen-1-ol (CAS RN 126-58-9) | 1.1.-31.12. | 500 tonnes | 0 % |
| 09.2565 | ex 2914 19 90 | 70 | Calcium acetylacetonate (CAS RN 19372-44-2) with a purity by weight of 95 % or more | 1.1.-31.12. | 400 tonnes | 0 % |
| 09.2852 | ex 2914 29 00 | 60 | Cyclopropyl methyl ketone (CAS RN 765-43-5) | 1.1.-31.12. | 300 tonnes | 0 % |
| 09.2638 | ex 2915 21 00 | 10 | Acetic acid (CAS RN 64-19-7) of a purity by weight of 99 % or more | 1.1.-31.12. | 1 000 000 tonnes | 0 % |
| 09.2679 | 2915 32 00 | | Vinyl acetate (CAS RN 108-05-4) | 1.1.-31.12. | 370 000 tonnes | 0 % |
| 09.2728 | ex 2915 90 70 | 85 | Ethyl trifluoroacetate (CAS RN 383-63-1) | 1.1.-31.12. | 400 tonnes | 0 % |
| 09.2665 | ex 2916 19 95 | 30 | Potassium (E,E)-hexa- 2,4-dienoate (CAS RN 24634-61-5) | 1.1.-31.12. | 8 250 tonnes | 0 % |
| 09.2684 | ex 2916 39 90 | 28 | 2,5-Dimethylphenylacetyl chloride (CAS RN 55312-97-5) | 1.1.-31.12. | 700 tonnes | 0 % |
| 09.2599 | ex 2917 11 00 | 40 | Diethyl oxalate (CAS RN 95-92-1) | 1.1.-31.12. | 500 tonnes | 0 % |
| 09.2769 | ex 2917 13 90 | 10 | Dimethyl sebacate (CAS RN 106-79-6) | 1.1.-31.12. | 1 000 tonnes | 0 % |
| 09.2634 | ex 2917 19 80 | 40 | Dodecanedioic acid (CAS RN 693-23-2), of a purity by weight of more than 98,5 % | 1.1.-31.12. | 8 000 tonnes | 0 % |
| 09.2540 | 2917 37 00 | 10 | Dimethyl terephthalate (CAS RN 120-61-6) with a purity by weight of 95 % or more | 1.1.-31.12. | 57 500 tonnes | 0 % |
| 09.2808 | ex 2918 22 00 | 10 | O-acetylsalicylic acid (CAS RN 50-78-2) | 1.1.-30.6. | 120 tonnes | 0 % |

| Order number | CN code | TARIC | Description | Quota period | Quota volume | Quota duty rate |
|--------------|---------------|-------|--|--------------|---------------|-----------------|
| 09.2646 | ex 2918 29 00 | 75 | Octadecyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl) propionate (CAS RN 2082-79-3) with: — a sieve passing fraction at a mesh width of 500 µm of more than 99 % by weight, and — a melting point of 49 C or more, but not more than 54 C, for use in the manufacture of PVC processing stabilizer-one packs based on powder mixtures (powders or press granulates) ⁽¹⁾ | 1.1.-31.12. | 380 tonnes | 0 % |
| 09.2647 | ex 2918 29 00 | 80 | Pentaerythritol tetrakis(3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate) (CAS RN 6683-19-8) with: — a sieve passing fraction at a mesh width of 250 µm of more than 75 % by weight and at a mesh width of 500 µm of more than 99 % by weight, and — a melting point of 110 C or more, but not more than 125 C, for use in the manufacture of PVC processing stabilizer-one packs based on powder mixtures (powders or press granulates) ⁽¹⁾ | 1.1.-31.12. | 140 tonnes | 0 % |
| 09.2975 | ex 2918 30 00 | 10 | Benzophenone- 3,3',4,4'-tetracarboxylic dianhydride (CAS RN 2421-28-5) | 1.1.-31.12. | 1 000 tonnes | 0 % |
| 09.2598 | ex 2921 19 99 | 75 | Octadecylamine (CAS RN 124-30-1) | 1.1.-31.12. | 400 tonnes | 0 % |
| 09.2649 | ex 2921 29 00 | 60 | Bis(2-dimethylaminoethyl)(methyl)amine (CAS RN 3030-47-5) | 1.1.-31.12. | 1 700 tonnes | 0 % |
| 09.2617 | ex 2921 42 00 | 89 | 4-Fluoro-N-(1-methylethyl)benzeneamine (CAS RN 70441-63-3) | 1.1.-31.12. | 500 tonnes | 0 % |
| 09.2602 | ex 2921 51 19 | 10 | O-phenylenediamine (CAS RN 95-54-5) | 1.1.-31.12. | 1 800 tonnes | 0 % |
| 09.2921 | ex 2922 19 00 | 22 | 2-(dimethylamino)ethyl acrylate (CAS RN 2439-35-2) with a purity by weight of 99 % or more | 1.1.-31.12. | 14 000 tonnes | 0 % |
| 09.2545 | ex 2922 29 00 | 63 | Acronifen (ISO) (CAS RN 74070-46-5) with a purity by weight of 97 % or more | 1.1.-31.12. | 4 000 tonnes | 0 % |

| Order number | CN code | TARIC | Description | Quota period | Quota volume | Quota duty rate |
|--------------|---------------|-------|--|--------------|----------------|-----------------|
| 09.2563 | ex 2922 41 00 | 30 | L-Lysine hydrochloride (CAS RN 657-27-2) or an aqueous solution of L-lysine (CAS RN 56-87-1), containing by weight 50 % or more of L-lysine, for use in the production of animal feed and/or for use in the production of pharmaceuticals ⁽¹⁾ | 1.1.-30.6. | 150 000 tonnes | 0 % |
| 09.2575 | ex 2923 90 00 | 87 | 3-Chloro-2-hydroxypropyl)trimethylammonium chloride (CAS RN 3327-22-8), in the form of an aqueous solution containing by weight 65 % or more but not more than 71 % 3-chloro-2-hydroxypropyl)trimethylammonium chloride | 1.1.-31.12. | 9 500 tonnes | 0 % |
| 09.2922 | ex 2923 90 00 | 88 | Aqueous solution containing by weight 78 % or more but not more than 82 % of [2-(acryloyloxy)ethyl]trimethylammonium chloride (CAS RN 44992-01-0) | 1.1.-31.12. | 10 000 tonnes | 0 % |
| 09.2854 | ex 2924 19 00 | 85 | 3-Iodoprop-2-yn-1-yl butylcarbamate (CAS RN 55406-53-6) | 1.1.-31.12. | 450 tonnes | 0 % |
| 09.2874 | ex 2924 29 70 | 87 | Paracetamol (INN) (CAS RN 103-90-2) | 1.1.-31.12. | 20 000 tonnes | 0 % |
| 09.2742 | ex 2926 10 00 | 10 | Acrylonitrile (CAS RN 107-13-1), for use in the manufacture of goods of chapter 55 and heading 6815 ⁽¹⁾ | 1.1.-31.12. | 30 000 tonnes | 0 % |
| 09.2583 | ex 2926 10 00 | 30 | Acrylonitrile (CAS RN 107-13-1), for use in the manufacture of goods of headings 2921, 2924, 3903, 3906, 3908, 3911 and 4002 ⁽¹⁾ | 1.1.-31.12. | 20 000 tonnes | 0 % |
| 09.2550 | ex 2926 90 70 | 31 | Lambda-cyhalothrin (ISO) (CAS RN 91465-08-6) with a purity by weight of 97 % or more | 1.1.-31.12. | 2 200 tonnes | 0 % |
| 09.2856 | ex 2926 90 70 | 84 | 2-Nitro-4(trifluoromethyl)benzonitrile (CAS RN 778-94-9) | 1.1.-31.12. | 900 tonnes | 0 % |
| 09.2685 | ex 2929 90 90 | 30 | Nitroguanidine (CAS RN 556-88-7) | 1.1.-31.12. | 6 500 tonnes | 0 % |
| 09.2597 | ex 2930 90 95 | 94 | Bis[3-(triethoxysilyl)propyl]disulphide (CAS RN 56706-10-6) | 1.1.-31.12. | 6 000 tonnes | 0 % |
| 09.2596 | ex 2930 90 95 | 96 | 2-Chloro-4-(methylsulphonyl)-3-((2,2,2-trifluoroethoxy)methyl) benzoic acid (CAS RN 120100-77-8) | 1.1.-31.12. | 300 tonnes | 0 % |

| Order number | CN code | TARIC | Description | Quota period | Quota volume | Quota duty rate |
|--------------|---------------|-------|--|--------------|-----------------|-----------------|
| 09.2580 | ex 2931 90 00 | 75 | Hexadecyltrimethoxysilane (CAS RN 16415-12-6) with a purity by weight of at least 95 %, for use in the manufacture of polyethylene (1) | 1.1.-31.12. | 165 tonnes | 0 % |
| 09.2842 | 2932 12 00 | | 2-Furaldehyde (furfuraldehyde) | 1.1.-31.12. | 10 000 tonnes | 0 % |
| 09.2696 | ex 2932 20 90 | 25 | Decan-5-olide (CAS RN 705-86-2) | 1.1.-31.12. | 6 000 kilograms | 0 % |
| 09.2697 | ex 2932 20 90 | 30 | Dodecan-5-olide (CAS RN 713-95-1) | 1.1.-31.12. | 6 000 kilograms | 0 % |
| 09.2812 | ex 2932 20 90 | 77 | Hexan-6-olide (CAS RN 502-44-3) | 1.1.-31.12. | 4 000 tonnes | 0 % |
| 09.2858 | 2932 93 00 | | Piperonal (CAS RN 120-57-0) | 1.1.-31.12. | 220 tonnes | 0 % |
| 09.2541 | 2933 19 90 | 73 | 2,4-Dihydro- 2,5-dimethyl-3H-pyrazol-3-one (CAS RN 2749-59-9) with a purity by weight of 99 % or more | 1.1.-31.12. | 150 tonnes | 0 % |
| 09.2543 | 2933 39 99 | 13 | Imazamox (ISO) (CAS RN 114311-32-9) with a purity by weight of 95 % or more | 1.1.-31.12. | 300 tonnes | 0 % |
| 09.2839 | ex 2933 39 99 | 09 | 2-(2-Pyridyl)ethanol (CAS RN 103-74-2) with a purity by weight of 99 % or more | 1.1.-31.12. | 700 tonnes | 0 % |
| 09.2546 | ex 2933 39 99 | 46 | Fluopicolide (ISO) (CAS RN 239110-15-7) with a content by weight of 97 % or more | 1.1.-31.12. | 250 tonnes | 0 % |
| 09.2547 | ex 2933 69 80 | 13 | Metribuzin (ISO) (CAS RN 21087-64-9) with a purity by weight of 93 % or more | 1.1.-31.12. | 225 tonnes | 0 % |
| 09.2860 | ex 2933 69 80 | 30 | 1,3,5-Tris[3-(dimethylamino)propyl]hexahydro- 1,3,5-triazine (CAS RN 15875-13-5) | 1.1.-31.12. | 600 tonnes | 0 % |
| 09.2566 | ex 2933 99 80 | 05 | 1,4,7,10-Tetraazacyclododecane (CAS RN 294-90-6) with a purity by weight of 96 % or more | 1.1.-31.12. | 60 tonnes | 0 % |
| 09.2544 | ex 2933 99 80 | 23 | Tebuconazole (ISO) (CAS RN 107534-96-3) with a purity by weight of 95 % or more | 1.1.-31.12. | 150 tonnes | 0 % |
| 09.2658 | ex 2933 99 80 | 73 | 5-(Acetoacetyl amino)benzimidazolone (CAS RN 26576-46-5) | 1.1.-31.12. | 400 tonnes | 0 % |

| Order number | CN code | TARIC | Description | Quota period | Quota volume | Quota duty rate |
|--------------|---------------|-------|--|--------------|------------------|-----------------|
| 09.2549 | ex 2934 99 90 | 16 | Difenoconazole (ISO) (CAS RN 119446-68-3) | 1.1.-31.12. | 1 000 tonnes | 0 % |
| 09.2548 | ex 2934 99 90 | 24 | Flufenacet (ISO) (CAS RN 142459-58-3) with a purity by weight of 95 % or more | 1.1.-31.12. | 900 tonnes | 0 % |
| 09.2593 | ex 2934 99 90 | 67 | 5-Chlorothiophene-2-carboxylic acid (CAS RN 24065-33-6) | 1.1.-31.12. | 45 000 kilograms | 0 % |
| 09.2675 | ex 2935 90 90 | 79 | 4-[[[(2-Methoxybenzoyl)amino]sulfonyl]benzoyl chloride (CAS RN 816431-72-8) | 1.1.-31.12. | 1 000 tonnes | 0 % |
| 09.2945 | ex 2940 00 00 | 20 | D-Xylose (CAS RN 58-86-6) | 1.1.-31.12. | 400 tonnes | 0 % |
| 09.2686 | ex 3204 11 00 | 75 | Colourant C.I. Disperse Yellow 54 (CAS RN 7576-65-0) and preparations based thereon with a colourant C.I. Disperse Yellow 54 content of 99 % or more by weight | 1.1.-31.12. | 250 tonnes | 0 % |
| 09.2676 | ex 3204 17 00 | 14 | Preparations based on Colourant C.I. Pigment Red 48:2 (CAS RN 7023-61-2) with a content thereof of 60 % or more but less than 85 % by weight | 1.1.-31.12. | 50 tonnes | 0 % |
| 09.2698 | ex 3204 17 00 | 30 | Colourant C.I. Pigment Red 4 (CAS RN 2814-77-9) and preparations based thereon with a colourant C.I. Pigment Red 4 content of 60 % or more by weight | 1.1.-31.12. | 150 tonnes | 0 % |
| 09.2659 | ex 3802 90 00 | 19 | Soda flux calcinated diatomaceous earth | 1.1.-31.12. | 35 000 tonnes | 0 % |
| 09.2908 | ex 3804 00 00 | 10 | Sodium lignosulphonate (CAS RN 8061-51-6) | 1.1.-31.12. | 40 000 tonnes | 0 % |
| 09.2889 | 3805 10 90 | | Sulphate turpentine | 1.1.-31.12. | 25 000 tonnes | 0 % |
| 09.2935 | ex 3806 10 00 | 10 | Rosin and resin acids obtained from fresh oleoresins | 1.1.-31.12. | 280 000 tonnes | 0 % |
| 09.2832 | ex 3808 92 90 | 40 | Preparation containing 38 % or more but not more than 50 % by weight of pyrrithione zinc (INN) (CAS RN 13463-41-7) in an aqueous dispersion | 1.1.-31.12. | 500 tonnes | 0 % |

| Order number | CN code | TARIC | Description | Quota period | Quota volume | Quota duty rate |
|--------------|---------------|-------|---|--------------|--------------|-----------------|
| 09.2923 | ex 3808 94 20 | 40 | Aqueous solution containing by weight: <ul style="list-style-type: none"> — 10,0 % or more but not more than 11,3 % of 5-chloro-2-methyl-2H-isothiazol-3-one, — 3,0 % or more but not more than 4,1 % of 2-methyl-2H-isothiazol-3-one, — a combined concentration of isothiazolones (CAS RN 55965-84-9) of 13,0 % or more but not more than 15,4 %, — 18 % or more but not more than 22 % of nitrates, calculated as sodium nitrate, and — 5 % or more but not more than 8 % of chlorides, calculated as sodium chloride | 1.1.-31.12. | 3 000 tonnes | 0 % |
| 09.2876 | ex 3811 29 00 | 57 | Additives consisting of reaction products of diphenylamine and branched nonenes with: <ul style="list-style-type: none"> — more than 20 % but not more than 50 % by weight 4-monononyldiphenylamine, and — more than 50 % but not more than 80 % by weight 4,4'-dinonyldiphenylamine, — a total percentage of 2,4-dinonyldiphenylamine and 2,4'-dinonyldiphenylamine of not more than 15 % by weight, used for the manufacture of lubricating oils ⁽¹⁾ | 1.1.-31.12. | 900 tonnes | 0 % |
| 09.2927 | ex 3811 29 00 | 83 | Additives containing by weight: <ul style="list-style-type: none"> — 70 % or more of 2,5-bis(tert-nonyldithio)-[1,3,4]-thiadiazole (CAS RN 89347-09-1), and — 10 % or more of 5-(tert-nonyldithio)-1,3,4-thiadiazole-2(3H)-thione (CAS RN 97503-12-3), for use in the manufacture of blends of additives for lubricating oils ⁽¹⁾ | 1.1.-31.12. | 500 tonnes | 0 % |
| 09.2814 | ex 3815 90 90 | 76 | Catalyst consisting of titanium dioxide and tungsten trioxide | 1.1.-31.12. | 3 000 tonnes | 0 % |

| Order number | CN code | TARIC | Description | Quota period | Quota volume | Quota duty rate |
|--------------|---------------|-------|---|--------------|---------------|-----------------|
| 09.2542 | 3824 99 92 | 97 | Mixture containing bis[3-(triethoxysilyl)propyl]polysulfides (CAS RN 211519-85-6) with a purity by weight of 84 % or more | 1.1.-31.12. | 2 000 tonnes | 0 % |
| 09.2644 | ex 3824 99 92 | 77 | Preparation containing by weight: — 55 % or more but not more than 78 % of dimethyl glutarate (CAS RN 1119-40-0), — 10 % or more but not more than 30 % of dimethyl adipate (CAS RN 627-93-0), and — not more than 35 % of dimethyl succinate (CAS RN 106-65-0) | 1.1.-31.12. | 10 000 tonnes | 0 % |
| 09.2907 | ex 3824 99 93 | 67 | Mixture of phytosterols, in the form of powder, containing by weight: — 75 % or more of sterols, — not more than 25 % of stanols, for use in the manufacture of stanols/sterols or stanol/sterol esters ⁽¹⁾ | 1.1.-31.12. | 2 500 tonnes | 0 % |
| 09.2568 | ex 3824 99 96 | 91 | Mixture, in pellet form, containing by weight: — 49 % or more but not more than 50 % of bis[3-(triethoxysilyl)propyl] polysulphides (CAS RN 211519-85-6), and — 50 % or more but not more than 51 % of carbon black (CAS RN 1333-86-4), of which 75 % by weight or more pass through a sieve with an aperture of 0,60 mm, but not more than 10 % pass through a sieve with an aperture of 0,25 mm (as determined by the ASTM D1511 method) | 1.1.-31.12. | 2 100 tonnes | 0 % |

| Order number | CN code | TARIC | Description | Quota period | Quota volume | Quota duty rate |
|--------------|---------------|-------|---|--------------|---------------|-----------------|
| 09.2820 | ex 3827 90 00 | 10 | Mixtures containing by weight: — 60 % or more but not more than 90 % of 2-chloropropene (CAS RN 557-98-2), — 8 % or more but not more than 14 % of (Z)-1-chloropropene (CAS RN 16136-84-8), — 5 % or more but not more than 23 % of 2-chloropropane (CAS RN 75-29-6), — not more than 6 % of 3-chloropropene (CAS RN 107-05-1), and — not more than 1 % of ethyl chloride (CAS RN 75-00-3) | 1.1.-31.12. | 6 000 tonnes | 0 % |
| 09.2671 | ex 3905 99 90 | 81 | Poly(vinyl butyral)(CAS RN 63148-65-2): — containing by weight 17,5 % or more, but not more than 20 % of hydroxyl groups, and — with a median particle size (D50) of more than 0,6 mm | 1.1.-31.12. | 12 500 tonnes | 0 % |
| 09.2846 | ex 3907 40 00 | 25 | Polymer blend of polycarbonate and poly(methyl methacrylate) with a polycarbonate content of not less than 98,5 % by weight, in the form of pellets or granules, with a luminous transmittance of not less than 88,5 %, measured using a test sample with a thickness of 4 mm at a wavelength of $\lambda = 400$ nm (according to ISO 13468-2) | 1.1.-31.12. | 2 000 tonnes | 0 % |
| 09.2585 | ex 3907 99 80 | 70 | Copolymer of poly(ethylene terephthalate) and cyclohexane dimethanol, containing more than 10 % by weight of cyclohexane dimethanol | 1.1.-31.12. | 60 000 tonnes | 2 % |
| 09.2855 | ex 3910 00 00 | 10 | Liquid poly(methylhydrosiloxane) with terminal trimethylsilyl groups (CAS RN 63148-57-2) with a purity by weight of 99,9 % or more | 1.1.-31.12. | 1 000 tonnes | 0 % |
| 09.2931 | ex 3911 90 11 | 10 | Poly(oxy- 1,4-phenylenesulphonyl- 1,4-phenyleneoxy- 1,4-phenyleneisopropylidene- 1,4-phenylene) (CAS RN 25135-51-7 and CAS RN 25154-01-2), in one of the forms mentioned in note 6(b) to this chapter containing by weight not more than 20 % of additives | 1.1.-31.12. | 6 300 tonnes | 0 % |

| Order number | CN code | TARIC | Description | Quota period | Quota volume | Quota duty rate |
|--------------|---------------|-------|--|--------------|---------------|-----------------|
| 09.2723 | ex 3911 90 19 | 35 | Poly(oxy- 1,4-phenylenesulfonyl- 1,4-phenyleneoxy- 4,4'-biphenylene) (CAS RNs 25608-64-4 and 25839-81-0) containing by weight not more than 20 % of additives | 1.1.-31.12. | 5 000 tonnes | 0 % |
| 09.2816 | ex 3912 11 00 | 20 | Cellulose acetate flakes | 1.1.-31.12. | 75 000 tonnes | 0 % |
| 09.2561 | ex 3912 39 85 | 60 | Hypromellose (INN) (CAS RN 9004-65-3), for use in the manufacturing of food supplements or pharmaceuticals (¹) | 1.1.-31.12. | 2 750 tonnes | 0 % |
| 09.2573 | ex 3913 10 00 | 20 | Sodium alginate extracted from brown seaweed (CAS RN 9005-38-3), with — a loss on drying of not more than 15 % by weight (4h at 105 C), — a water-insoluble fraction of not more than 2 % by weight, calculated on the dry weight | 1.1.-31.12. | 2 000 tonnes | 0 % |
| 09.2641 | ex 3913 90 00 | 87 | Sodium hyaluronate, non sterile, with: — a weight average molecular weight (M_w) of not more than 900 000, — an endotoxin level of not more than 0,008 Endotoxin units (EU)/mg, — an ethanol content of not more than 1 % by weight, — an isopropanol content of not more than 0,5 % by weight | 1.1.-31.12. | 300 kilograms | 0 % |
| 09.2661 | ex 3920 51 00 | 50 | Sheets of polymethylmethacrylate conforming to standards: — EN 4364 (MIL-P-5425E) and DTD5592A, or — EN 4365 (MIL-P-8184) and DTD5592A | 1.1.-31.12. | 100 tonnes | 0 % |
| 09.2645 | ex 3921 14 00 | 20 | Cellular block of regenerated cellulose, impregnated with water containing magnesium chloride and quaternary ammonium compounds, measuring 100 cm (± 10 cm) x 100 cm (± 10 cm) x 40 cm (± 5 cm) | 1.1.-31.12. | 1 700 tonnes | 0 % |

| Order number | CN code | TARIC | Description | Quota period | Quota volume | Quota duty rate |
|--------------|--------------------------------|----------|---|--------------|-------------------------|-----------------|
| 09.2572 | ex 5205 26 00 ex 5205 27 00 | 10 10 | Raw white single cotton yarn — of combed fibres, — with an average fibre length of 36,5 mm or more, — produced through the compact ring spinning process with pneumatic compression, — with a tear strength of 26,5 cN/tex or more (according to ISO 2062:2009, at a speed of 5 000 mm/min) | 1.1.-31.12. | 50 000 tonnes | 0 % |
| 09.2848 | ex 5505 10 10 | 10 | Waste of synthetic fibres (including noils, yarn waste, and garnetted stock) of nylon or other polyamides (PA6 and PA66) | 1.1.-31.12. | 10 000 tonnes | 0 % |
| 09.2721 | ex 5906 99 90 | 20 | Woven and laminated rubberised textile fabric with the following characteristics: — with three layers, — one outer layer consists of acrylic fabric, — the other outer layer consists of polyester fabric, — the middle layer consists of chlorobutyl rubber, — the middle layer has a weight of 452 g/m ² or more but not more than 569 g/m ² , — the textile fabric has a total weight of 952 g/m ² or more but not more than 1 159 g/m ² , and — the textile fabric has a total thickness of 0,8 mm or more but not more than 4 mm, used for the manufacture of the retractable roof of motor vehicles ⁽¹⁾ | 1.1.-31.12. | 375 000 square meters | 0 % |
| 09.2628 | ex 7019 66 00 | 10 | Glass web woven from glass fibre coated in plastic, of a weight of 120 g/m ² (± 10 g/m ²), of a type used in rolling insect screens with fixed frames | 1.1.-31.12. | 3 000 000 square meters | 0 % |

| Order number | CN code | TARIC | Description | Quota period | Quota volume | Quota duty rate |
|--------------|--------------------------|-------|--|--------------|-----------------------|-----------------|
| 09.2652 | ex 7410 11 00 | 50 | Refined copper foil and strips, electrolytically manufactured, with a thickness of 0,015 mm or more but not more than 0,150 mm, used for the manufacture of laminates for Printed Circuit Boards and of Printed Circuit Boards in the printed circuit board industry ⁽¹⁾ | 1.1.-31.12. | 1 020 tonnes | 0 % |
| 09.2662 | ex 7410 21 00 | 55 | Plates: — consisting of at least one layer of fibreglass fabric impregnated with epoxide resin, — covered on one or both sides with copper foil with a thickness of not more than 0,15 mm, — with a dielectric constant (DK) of less than 5,4 at 1 MHz, as measured according to IPC-TM-650 2.5.5.2, — with a loss tangent of less than 0,035 at 1 MHz, as measured according to IPC-TM-650 2.5.5.2, — with a comparative tracking index (CTI) of 600 or more | 1.1.-31.12. | 108 000 square meters | 0 % |
| 09.2795 | 7601 20 30 7601 20 40 | | Slabs and billets of unwrought aluminium alloys | 1.1.-31.12. | 573 000 tonnes | 4 % |
| 09.2835 | ex 7604 29 10 | 30 | Aluminium alloy rods with a diameter of 300,1 mm or more, but not more than 533,4 mm | 1.1.-31.12. | 1 000 tonnes | 0 % |

| Order number | CN code | TARIC | Description | Quota period | Quota volume | Quota duty rate |
|--------------|--|----------------------|--|--------------|------------------|-----------------|
| 09.2736 | ex 7607 11 90 ex 7607 11 90 ex 7607 11 90 ex 7607 11 90 | 75 77 78 79 | Aluminium and magnesium alloy strip or foil: — of an alloy conforming to standards 5182-H19 or 5052-H19, — in rolls with an outside diameter of minimum 1 250 mm but not more than 1 350 mm, — of a thickness (tolerance - 0,006 mm) of 0,15 mm, 0,16 mm, 0,18 mm or 0,20 mm, — of a width (tolerance \pm 0,3 mm) of 12,5 mm, 15,0 mm, 16,0 mm, 25,0 mm, 35,0 mm, 50,0 mm or 356 mm, — having a camber tolerance of not more than 0,4 mm/750 mm, — of a flatness measurement: I-unit \pm 4, — having a tensile strength of more than (5182-H19) 365 MPa or (5052-H19) 320 MPa, and — of an elongation A50 of more than (5182-H19) 3 % or (5052-H19) 2,5 %, for use in the manufacture of slats for blinds (¹) | 1.1.-31.12. | 600 tonnes | 0 % |
| 09.2722 | 8104 11 00 | | Unwrought magnesium, containing at least 99,8 % by weight of magnesium | 1.1.-31.12. | 120 000 tonnes | 0 % |
| 09.2840 | ex 8104 30 00 | 20 | Magnesium powder: — of purity by weight of 98 % or more, but not more than 99,5 %, and — with a particle size of 0,2 mm or more but not more than 0,8 mm | 1.1.-31.12. | 2 000 tonnes | 0 % |
| 09.2629 | ex 8302 49 00 | 91 | Aluminium telescopic handle for use in the manufacture of luggage (¹) | 1.1.-31.12. | 1 500 000 pieces | 0 % |
| 09.2720 | ex 8413 91 00 | 50 | Pump head for two cylinder high pressure pump made of forged steel, with: — milled threaded fittings with a diameter of 10 mm or more but not more than 36,8 mm, and — drilled fuel channels with a diameter of 3,5 mm or more but not more than 10 mm, of a kind used in diesel injection systems | 1.1.-31.12. | 65 000 pieces | 0 % |

| Order number | CN code | TARIC | Description | Quota period | Quota volume | Quota duty rate |
|--------------|---------------|-------|---|--------------|------------------|-----------------|
| 09.2569 | ex 8414 90 00 | 80 | Turbocharger wheel housing of cast aluminium alloy or cast iron: — with a heat resistance up to 400 °C, — with a hole of 30 mm or more but not more than 300 mm for the insertion of the compressor wheel, for use in the automotive industry ⁽¹⁾ | 1.1.-31.12. | 4 000 000 pieces | 0 % |
| 09.2570 | ex 8482 91 90 | 10 | Rollers with a logarithmic profile and a diameter of 25 mm or more but not more than 70 mm or balls with a diameter of 30 mm but not more than 100 mm, — made of 100Cr6 steel or 100CrMnSi6-4 steel (ISO 3290), — with a deviation of 0,5 mm or less as determined with the FBHmethod for use in wind turbine industry ⁽¹⁾ | 1.1.-31.12. | 600 000 pieces | 0 % |
| 09.2562 | ex 8482 99 00 | 30 | Brass cages with the following characteristics: — continuously or centrifugally cast, — turned, — containing by weight 35 % or more, but not more than 38 % of zinc, — containing by weight 0,75 % or more, but not more than 1,25 % of lead, — containing by weight 1,0 % or more, but not more than 1,4 % of aluminium, and — with a tensile strength of 415 Pa or more, of a kind used for the manufacture of ball bearings | 1.1.-31.12. | 550 000 pieces | 0 % |

| Order number | CN code | TARIC | Description | Quota period | Quota volume | Quota duty rate |
|--------------|---------------|-------|--|--------------|------------------|-----------------|
| 09.2557 | ex 8482 99 00 | 60 | Inner or outer rings made of steel, not hardened or not grinded, outer ring with internal raceway(s), inner ring with external raceway(s), with external diameters of: — 14 mm or more but not more than 77 mm for the inner ring, — 26 mm or more but not more than 101 mm for the outer ring, for use in the manufacture of bearings ⁽¹⁾ | 1.1.-31.12. | 2 000 pieces | 0 % |
| 09.2552 | ex 8482 99 00 | 70 | Male and female parts of cages, — made of flat-rolled steel, — with a diameter of 14,5 mm or more but not more than 420 mm, — the male part including rivets, — the female part including holes, used for manufacturing of deep groove ball bearings ⁽¹⁾ | 1.1.-31.12. | 1 221 tonnes | 0 % |
| 09.2553 | ex 8482 99 00 | 80 | Punched cages of various diameters, — made of flat rolled steel, — with tensile strength of 270 MPa or more, for the production of tapered roller bearings ⁽¹⁾ | 1.1.-31.12. | 8 000 000 pieces | 0 % |

| Order number | CN code | TARIC | Description | Quota period | Quota volume | Quota duty rate |
|--------------|--------------------------------|----------|---|--------------|------------------|-----------------|
| 09.2560 | ex 8501 31 00 | 85 | Power transmission device for controlling the output of exhaust gas turbochargers, consisting of: — a DC motor of an output not exceeding 600 W, — for usage with a supply voltage of 8 V or more but no more than 48 V, — with motor connection (plug-in connection), — whether or not with position sensor, — whether or not with integrated control and power electronics, — whether or not with spring mechanism for resetting the lever, — built in a housing with reduction gear and lever attached to the motor drive shaft, or — built in a housing with threads integrated into the rotor of the motor for linear movement of the integrated control rod | 1.1.-31.12. | 650 000 pieces | 0 % |
| 09.2559 | ex 8501 40 20 ex 8501 40 80 | 70 70 | Electric AC motor, single-phase, whether or not with commutator — with a nominal output of 180 W or more, — with an input power of 150 W or more but not more than 2 700 W, — with an external diameter of more than 44,8 but not more than 135,2 mm, — with a rated speed of more than 10 000 rpm but not more than 50 000 rpm, — whether or not equipped with air-inducting ventilator, — whether or not with mechanical device (pinion, screws, gear connection etc.) on the shaft, for use in the manufacture of domestic appliances ⁽¹⁾ | 1.1.-31.12. | 2 000 000 pieces | 0 % |

| Order number | CN code | TARIC | Description | Quota period | Quota volume | Quota duty rate |
|--------------|---|----------------|---|--------------|--------------|-----------------|
| 09.2554 | ex 8505 11 10 ex 8505 11 90 ex 8505 19 90 | 74 74 74 | Articles in shape of flat bars, arched bars, quarter sleeves or trapezoid whether or not arched, rounded corners or oblique sides made of ferrite, or cobalt, or samarium or other rare-earth metals, or their alloy, — whether or not overmolded with polymers, — whether or not coated or passivated with a surface treatment, with: — a length of 5 mm or more, but not more than 60 mm, — a width of 5 mm or more, but not more than 40 mm, — a thickness of 3 mm or more, but not more than 15 mm, intended to become permanent magnets after magnetisation | 1.1.-31.12. | 460 tonnes | 0 % |
| 09.2555 | ex 8505 11 10 | 76 | Articles of an alloy of neodymium, or an alloy of samarium, — whether or not coated or passivated with a surface treatment, — whether or not covered with zinc, — in the shape of rectangles, with: — a length of 13,8 mm or more but not more than 45,2 mm, — a width of 7,8 mm or more but not more than 25,2 mm, — a height of 1,3 mm or more but not more than 4,7 mm, intended to become permanent magnets after magnetisation | 1.1.-31.12. | 350 tonnes | 0 % |
| 09.2556 | ex 8505 11 10 | 77 | Article of an alloy of neodymium, in the form of arched rectangles, whether or not coated or passivated with a surface treatment, with: — a width of 9,1 mm or more but not more than 10,5 mm, — a length of 20 mm or more but not more than 30,1 mm, intended to become permanent magnets after magnetization | 1.1.-31.12. | 50 tonnes | 0 % |

| Order number | CN code | TARIC | Description | Quota period | Quota volume | Quota duty rate |
|--------------|---|----------------|--|--------------|----------------|-----------------|
| 09.2574 | ex 8537 10 91 | 73 | Multifunctional device (instrument cluster) with: — curved TFT LCD display (radius 750 mm) with touch-sensitive surfaces, — microprocessors and memory chips, — acoustic module and loudspeaker, — connections for CAN, 3 x LIN bus, LVDS and Ethernet, — for operating various functions (e.g. chassis, lighting) and — for situation-related display of vehicle and navigation data (e.g. speed, odometer, charge level of the drive battery), for use in the manufacture of passenger cars powered solely by an electric motor covered by HS subheading 8703 80 ⁽¹⁾ | 1.1.-31.12. | 66 900 pieces | 0 % |
| 09.2558 | ex 8543 70 90 | 87 | An electronic sound generator, creating an analog signal for a device producing the sound of an engine, containing: — a printed circuit board with a microprocessor and a sound amplifier, — a connector, — a plastic housing, — with or without a metal holder, for use in the manufacture of goods of Chapter 87 ⁽¹⁾ | 1.1.-31.12. | 30 000 pieces | 0 % |
| 09.2910 | ex 8708 99 97 | 75 | Aluminium alloy support bracket, with mounting holes, whether or not with fixation nuts, for indirect connection of the gearbox to the car body for use in the manufacture of goods of Chapter 87 ⁽¹⁾ | 1.1.-31.12. | 200 000 pieces | 0 % |
| 09.2668 | ex 8714 91 10 ex 8714 91 10 ex 8714 91 10 | 21 31 75 | Bicycle frame, constructed from carbon fibres and artificial resin, for use in the manufacture of bicycles (including electric bicycles) ⁽¹⁾ | 1.1.-31.12. | 600 000 pieces | 0 % |

| Order number | CN code | TARIC | Description | Quota period | Quota volume | Quota duty rate |
|--------------|---------------|-------|---|--------------|------------------|-----------------|
| 09.2564 | ex 8714 91 10 | 25 | Frame, constructed from aluminium or aluminium and carbon fibres and artificial resin, for the use in the manufacture of bicycles (including electric bicycles) ⁽¹⁾ | 1.1.-31.12. | 9 600 000 pieces | 0 % |
| | ex 8714 91 10 | 35 | | | | |
| | ex 8714 91 10 | 77 | | | | |
| 09.2579 | ex 9029 20 31 | 40 | Clustered instrument panel with: — stepping motors, — analog pointers and dials, — or without microprocessor control board, — or without LED indicators or LCD display, — showing at least: — speed, — engine revolutions, — engine temperature, — the fuel level, — communicating via CAN-BUS and/or K-LINE protocols, for use in the manufacture of goods of Chapter 87 ⁽¹⁾ | 1.1.-31.12. | 160 000 pieces | 0 % |
| | ex 9029 90 00 | 40 | | | | |

⁽¹⁾ Suspension of duties is subject to end-use customs supervision in accordance with Article 254 of Regulation (EU) No 952/2013.

⁽²⁾ However, the suspension of tariff duties does not apply where the processing is carried out by retail or catering undertakings.'

| G.T.P | Dipnot | Eşyanın Tanımı | Birim | Miktarı | Gümrük Vergisi % |
|------------------|--------|---|-------|---------|------------------|
| 2712.20.90 | * | Parafin | Ton | 10.000 | 0 |
| 2811.19.80.90.19 | * | *Ağırlıkça % 98,5 veya daha fazla saflıkta fosforöz asit (CAS RN 13598-36-2). | Ton | 2.000 | 0 |
| 2914.19.90 | * | *Minimum %99,5 saflıkta ve aşağıdaki özelliklerde asetilaseton (CAS RN 123-54-6): maksimum % 0,1 asetik asit içeren, maksimum % 0,1 su içeren, maksimum 15 APHA renk değerinde, kırınma indisi $1,450 \pm 0,002$ yoğunluğu: $0,970 - 0,975 \text{ g/cm}^3$ (20°C). | Ton | 1.100 | 0 |
| 2915.21 | * | *Ağırlıkça %99 veya daha fazla saflıkta asetik asit (CAS RN 64-19-7). | Ton | 70.000 | 0 |
| 2915.32 | * | Vinil Asetat. | Ton | 107.000 | 0 |
| 2916.12.00.00.13 | * | Butil Akrilat (CAS RN 141-32-2). | Ton | 65.000 | 0 |
| 2926.10 | * | *55 fasıl ve 68.15 GTP'li ürünlerin üretiminde kullanılan akrilonitril. | Ton | 120.000 | 0 |
| 2931.90.00 | * | *Tekstil apreleme malzemesinin hammaddesi olarak kullanılan ağırlıkça %99 veya daha fazla saflıkta oktametilsiklotetrasiloksan (CAS RN 556-67-2). | Ton | 5.000 | 0 |
| 2932.20.90 | * | *Epsilon-Kaprolakton. | Ton | 800 | 0 |
| 3804.00 | * | *Kuru ağırlığı hesaplandığında %55 veya daha fazla sodyum lügnosülfonat içeren sodyum lügnosülfonat sulu çözeltisi. | Ton | 1.800 | 0 |
| 3815.19.90 | *,a | Dizel üretiminde organik ve inorganik safsızlıklara karşı kullanılan, tek bileşenler veya set halinde ithal edilen, aşağıdaki müstahzarlardan en az birinden oluşan katalizör sistemi bileşenleri: - seramik malzeme (CAS RN 66402-68-4), - alüminyum oksit üzerinde desteklenen molibden oksit ve nikel oksit, - alüminyum oksit üzerinde desteklenen molibden oksit, nikel oksit, alüminyum fosfat, silika, molibden, su ve organik katkı maddesi, - alüminyum oksit üzerinde desteklenen molibden oksit, nikel oksit, alüminyum fosfat, zayıf organik asit, metal oksit ve su, - alüminyum oksit üzerinde desteklenen molibden oksit, alüminyum fosfat, zayıf organik asit, su ve kobalt oksit. | Ton | 800 | 0 |
| 3903.30 | * | *Çamaşır makinesi, bulaşık makinesi ve buzdolabı iç ve dış aksam parçalarının üretiminde kullanılan kendinden renkli, UV dayanımı ve antistatik özelliklere sahip aşağıdakileri içeren; - Gerilme katsayısı 2250 MPa (Megapascal) veya daha fazla fakat 2270 MPa dan az olan (ISO 527 metoduna göre belirlenmiş), - Kopmada gerilme dayanımı % 25 (ISO 527 ye göre belirlenmiş), - 220 °C 'de 10 kg'ının erime akış hızı 10g/10dk veya daha fazla fakat 21 g/10dk' dan az olan (ISO 1133 e göre belirlenmiş), - Renk değeri ISO 11664-4 test metoduna göre belirlenmiş; • "L" değeri 92,80 eşit veya daha fazla ve 94'e eşit veya | Ton | 4.000 | 0 |

| G.T.P | Dipnot | Eşyanın Tanımı | Birim | Miktarı | Gümrük Vergisi % |
|------------------|--------|---|-------|------------|------------------|
| | | daha az olmalı, • “a” değeri -006’ya eşit veya daha fazla ve -3,02’ye eşit veya daha az olmalı, • “b” değeri -0,62’ye eşit veya daha fazla ve -1,82’ye eşit veya daha az olmalıdır akrilonitril butadien stiren kopolimeri. | | | |
| 3907.29.20 | * | *(NJ 406) Tolüen diammin ve propilen oksit reaksiyonu sonucu elde edilen polieter polyol (OH 380-415 mg KOH/g,Vizkosite: 15000-20000 mPas). | Ton | 2.200 | 0 |
| 3907.29.20 | * | *(NJ 4502) Sükroz-gliserol ve propilen oksit reaksiyonu sonucu elde edilen polieter polyol (OH 430-470, Vizkosite:15000-20000 mPas). | Ton | 14.500 | 0 |
| 7606.12.99 | *,a | NADCAP ve AS9100 sertifikalı, 7040 serisi alüminyum alaşımlı levha: -193.746 mm2’den yüksek katı dikdörtgen kesit alanı için 130mm veya daha fazla fakat 149mm’den fazla olmayan bir kalınlığa veya -166.203 mm2’den yüksek katı dikdörtgen kesit alanı için 150 mm veya daha fazla ancak 180 mm’den fazla olmayan bir kalınlığa sahip havacılık endüstrisi ürünlerinin imalinde kullanılmaya mahsus. | Ton | 30 | 0 |
| 8414.30.81.90.00 | *,a | *Rotatif (rotary) tip kompresör, soğutma kapasitesi 2 kW ile 8kW arasında olan tek veya üç fazlı motora sahip, R32 veya R410 tip refrijeran sıvı kullanan, klimaların üretimine mahsus olan. | Adet | 2.000.000 | 0 |
| 8504.31.80 | *,a | Elektrik transformatörü: - güç taşıma kapasitesi 1 kVA'yı geçmeyen, - bir ferrit nüveye sahip, - fiş veya kablosu olmayan, - sıvı izolasyonu olmayan, Çamaşır makineleri, çamaşır kurutma makineleri, bulaşık makineleri, fırınlar, klimalar, buzdolapları ve termosifonların imalatında güç ve kontrol kartları için dahili olarak kullanılmaya mahsus. | Adet | 13.000.000 | 0 |
| 8504.31.80 | *,a | Elektrik transformatörü: • güç taşıma kapasitesi 1 kVA'yı geçmeyen, • fiş veya kablosu olmayan, • sıvı izolasyonu olmayan, TV'lerin, VS'lerin (görsel çözümler, monitör, akıllı tahta) ve set üstü kutuların imalatında dahili olarak kullanılmaya mahsus. | Adet | 10.000.000 | 0 |
| 8507.50.00 | *,a | *Nikel—metal hidrit (NiMh) akümülatörler: -voltajı 150 V veya daha fazla olan ancak, 300 V'u geçmeyen, -uzunluğu 220 mm veya fazla olan ancak, 500 mm'yi | Adet | 185.000 | 0 |

| G.T.P | Dipnot | Eşyanın Tanımı | Birim | Miktarı | Gümrük Vergisi % |
|--|--------|---|-------|------------|------------------|
| | | geçmeyen, -genişliği 500 mm veya daha fazla olan ancak, 1125 mm'yi geçmeyen, -yüksekliği 100 mm veya daha fazla olan ancak, 235 mm'yi geçmeyen, 87. fasılda yer alan motorlu taşıtların imalinde kullanılmaya mahsus . | | | |
| 8507.60.00 veya 8507.80.00 | *,a | *Yeniden şarj edilebilir lityum iyon polimer piller (batarya): -nominal kapasitesi 1 060 mAh olan, -nominal gerilimi 7,4 V (ortalama gerilimi 0,2 C'de deşarj) olan, -8,4 V'luk ($\pm 0,05$) voltajı olan, -uzunluğu 86,4 mm ($\pm 0,1$) olan, -genişliği 45 mm ($\pm 0,1$) olan, -yüksekliği 11 mm ($\pm 0,1$) olan, yazar kasaların imalinde kullanılmaya mahsus . | Adet | 100.000 | 0 |
| 8507.60.00 | *,a | *Lityum-iyon akümülatör: -Kalınlığı 6 mm'den fazla olmayan, -Genişliği 100 mm'den fazla olmayan, -Uzunluğu 150,15 mm'den fazla olmayan, - Nominal kapasitesi 1.000 mAh veya daha fazla olan ancak, 10.000 mAh'den fazla olmayan, -Ağırlığı 150 gr'dan fazla olmayan, 8517.13.00 alt başlığında yer alan ürünlerin imalinde kullanılmaya mahsus. | Adet | 11.000.000 | 0 |
| 8507.60.00 | *,a | *Lityum İyonlu (Li-Ion) Akümülatörler: -Voltajı 150 V veya daha fazla olan ancak, 300 V'u geçmeyen, -Uzunluğu 290 mm veya daha fazla olan ancak 490 mm'yi geçmeyen, -Genişliği 670 mm veya daha fazla olan ancak 1120 mm'yi geçmeyen, -Yüksekliği 140 mm veya daha fazla olan ancak 230 mm'yi geçmeyen, 87. fasılda yer alan motorlu taşıtların imalinde kullanılmaya mahsus . | Adet | 138.000 | 0 |
| 8529.90.93.00.00 veya 8539.51.00.00.00 9405.41.31.00.00 9405.42.31.00.00 9405.49.40.00.00 | *,a | *Yalnız LED Diyotlu Baskılı Devre Kartı; prizmalar/lensler ile donatılmış olsun ya da olmasın, bağlayıcı(lar) ile donatılmış olsun ya da olmasın, 85.28 başlığındaki ürünlerin arka ışık ünitelerinin imaline mahsus. | Adet | 40.000.000 | 0 |
| 9503.00.75 | *,a | *Aşağıdaki özelliklere sahip kare veya dikdörtgen şeklinde baskı devre kartları: - plastikten yapılmış bir gövde, - ön tarafında voltaj kontrolü sağlayan bir potansiyometre, - komutları iletmek için devre kartlarına bağlı renkli kablolar oyuncakların (arabaların) imalinde kullanılmaya mahsus. | Adet | 5.000.000 | 0 |

| G.T.P | Dipnot | Eşyanın Tanımı | Birim | Miktarı | Gümrük Vergisi % |
|------------|--------|--|-------|-----------|------------------|
| 9503.00.95 | *,a | *Aşağıdaki özelliklere sahip ses mekanizması: - plastikten yapılmış bir gövde (genellikle ten renginde), - gövdenin üst kısmında hoparlör delikleri, - gövdenin altında bir yalıtım şeridi, - yalıtım şeridi çıkarıldıktan sonra gövdenin üst kısmına bastırılarak çalışan bir mekanizma, - düğmeye basıldığında çalan önceden yüklenmiş sesler oyuncakların (oyuncak bebeklerin) imalinde kullanılmaya mahsus. | Adet | 3.000.000 | 0 |

*: Bu GTP'lerde sadece eşya tanımı sütununda özellikleri belirtilen ürünler için vergi oranı düşürülmüştür.

(a) Bu GTP'lerde sadece eşya tanımı sütununda belirtilen amaçlar için vergi oranı düşürülmüştür; bu eşya gümrük mevzuatının nihai kullanıma ilişkin hükümlerine tabidir.